



FARM OIL 15W/40

Hi-Tec Farm Oil 15W/40 is a premium Super Tractor Oil Universal (STOU) specifically formulated to service tractors with just one lubricant where formerly up to four or more oils were required.



UNIVERSAL TRANS PLUS 10W/30

Hi-Tec Iniversal Trans Plus 10W/30 is a new generation Universal Tractor Transmission Oil (UTTO) specially designed to meet the Case MAT 3540 performance level required by many modern CVT equipped tractors. It is also suitable for use in a wide range of power-driven agricultural equipment fitted with gears, transmissions, differentials, final drives, hydraulic pumps, hydraulic bearings, wet brakes, and power take-off (PTO) clutches. It is suitable for use in a large range of equipment produced by major OEMs including John Deere, Massey Ferguson, New Holland, Case, Allison, Caterpillar, Komatsu, Kubota, Denison, Sperry Vickers, Plessey and Sundstrand. Please contact your Hi-Tec Oils Representative for the relevant performance levels.



UNIVERSAL TRANS 10W/30

Hi-Tec Universal Trans is an 10W/30 new generation hydraulic/transmission Universal Tractor Transmission Oil (UTTO) designed for a wide range of power-driven agricultural equipment fitted with gears, transmission, differentials, final drives, hydraulic pumps, hydraulic bearings, wet brakes, and power take-off (PTO) clutches.



UNIVERSAL TRANS 10W/20

Hi-Tec Universal Trans 10W/20 is a new generation hydraulic/transmission Universal Tractor Transmission Oil (UTTO) designed for a wide range of power-driven agricultural equipment fitted with gears, transmissions, differentials, final drives, hydraulic pumps, hydraulic bearings, wet brakes, and power take-off (PTO) clutches.



DD50 COOLANT GREEN

Hi-Tec DD50 Coolant Green is a premixed heavy duty Hybrid technology diesel engine coolant. This low silicate, phosphate and amine free product is recommended for use in automotive, light duty and heavy-duty on-road truck, off-road, farm and marine diesel applications. It provides excellent high temperature aluminum protection and is suitable for use in hard water. It is compatible with both conventional and OAT coolants. It has an extended life of 6 years; 12,000 hours or 1,000,000 km whichever comes first.



HYDRAULIC OILS ISO 32, 46 & 68

Hi-Tec Hydraulic Oils are blended from superior, high quality mineral oils possessing a high viscosity index and low pour point. These oils give a long trouble free service life and will be chemically stable under severe operating conditions. They provide excellent protection against corrosion; resist emulsification, and any formation of unwanted stable foam.

Also available in ISO 10, 22, 100, 150

SPECIFICATIONS

Product Code	HI3-2691
API	Diesel CG-4, CF, CE, CD, Petrol SF, SE; GL-4
ACEA	E2
Performance	Caterpillar TO-2; John Deere JDM J27D and J20C; Meets most tractor OEM specifications, as well as many hydraulic pump and transmission specifications.
Product Sizes	5L, 20L, 200L, 1000L and Bulk

SPECIFICATIONS

Product Code	HI3-2692
API	GL-4
Performance	John Deere JDM J20C New Holland ESN-M2C134-D, FNHA-2-C-200.00; Massey Ferguson M-1145, 1143, 1141, 1135; Case MS-1209, 1207, 1210, 1230, MAT 3505/3525/3526/3540; Kubota; White Farm (Oliver); AGCO/Deutz-Allis/Allis Chalmers; Volvo; Clark; ZF.
Product Sizes	5L, 20L, 200L, 1000L and Bulk

SPECIFICATIONS

Product Code	HI3-2694
API	GL-4
Performance	John Deere JDM J20C; New Holland ESN-M2C134-D, FNHA-2-C-200.00; Massey Ferguson M-1145, 1143, 1141, 1135; Case MS-1209, 1207, 1210, 1230, MAT 3505/3525/3526; Kubota; White Farm (Oliver); AGCO/Deutz-Allis/Allis Chalmers; Volvo; Clark; ZF
Product Sizes	1L, 5L, 20L, 200L, 1000L and Bulk

SPECIFICATIONS

Product Code	HI3-2696
API	GL-4
Performance	John Deere JDM J20C; New Holland ESN-M2C134-D, FNHA-2-C-200.00; Massey Ferguson M-1145, M-1143, M-1141, M-1135; Case MS-1209, MS-1207, MS-1210, MS-1230; Kubota, White Farm (Oliver), AGCO/ Deutz-Allis/ Allis-Chalmers; Volvo, Clark, ZF
Product Sizes	20L, 200L, 1000L and Bulk

SPECIFICATIONS

Product Code	HI8-3090
Performance	ASTM D-3306, D-4985, D-6210; MAN M324; Caterpillar EC1; Mercedes Benz DBL 325; Cummins 14603; MTU MTL 5048; Detroit Diesel 7SE 298; New Holland WSN-M97B18-D; Daimler Chrysler MS 7170, MS 9769; PACCAR; Ford ESE M97B44A, ESE-M97B18-C, Ford WSS-M97B51-A1; Peterbilt 8502.002; Freightliner 48-2288D; Perkins; GM 1825M, 1899M; GM Heavy Truck; Saab-Scania 6901; Hyundai; SAE J1034, J1941; JIS K2234 TMC RP 329; Kenworth R026-170-97; Volvo Heavy Truck; Landrover; White Star; MACK Trucks; US Federal A-A-870-A; Deutz 0199-99-1115/6; Kubota Extended Life Premix Coolant
Product Sizes	20L, 200L and 1000L

SPECIFICATIONS

Product Code	HI5-2712 (ISO32); HI5-2714 (ISO46); HI5-2716 (ISO68)
Performance	Vickers I-286-S, M-2950-S; AFNOR NFE 48-603 (HM); Hagglunds-Denison HF-0, HF-1, HF-2; AFNOR NFE 48-691 (wet); Cincinnati Milacron P-68, P-69, P-70; SS155434; DIN 51524, Part 2; ISO 6743/4 (HM); US Steel 136, 127; SEB 181 222; Racine, variable volume vane pumps; VDMA 24318; Commercial Hydraulics; ASTM D6158-05, ISO 11158 (HM)
Product Sizes	10L (ISO68), 20L, 200L, 1000L and Bulk