



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

### FLEETMASTER MONOGRADES CF 10W, SAE 30, 40 & 50

#### PRODUCT DESCRIPTION

Hi-Tec Fleetmaster Monograde oils are available in **SAE 10W, 30, 40, & 50** grades. They are high performance diesel engine oils suitable for either turbo-charged or normally aspirated applications.

Hi-Tec Fleetmaster Monograde oils are uniquely formulated to promote the highest of standards of engine cleanliness in modern diesel engines requiring a monograde oil.

The SAE 40 is specifically required for Detroit Diesel 2 Stroke engines and can also be used in commercial mixed fleets as well as mining and construction equipment.

**Always consult to your vehicle owner's manual for the manufacturers recommendations.**

#### BENEFITS

- Bore polishing minimal
- Detergent/Dispersants keeping engine clean
- Antiwear characteristics
- Rust and Corrosion protection
- Engine Cleanliness
- Reduced ring sticking at high temperatures

#### SPECIFICATIONS

API: CF-2, CF, SG, SF

ACEA: E2 (2004)

Mercedes Benz: MB 227.0, 228.0 blanket

MAN 270

Suitable for use in Detroit Diesels



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

### TYPICAL PROPERTIES

PROPERTY	ASTM METHOD	RESULTS			
		10W	30	40	50
SAE					
Product Code		2239	2240L	2241	2242
Density Kg/Lt @ 15°C	ASTM D-1298	0.876	0.894	0.899	0.903
Viscosity cSt @ 100°C	ASTM D-445	5.60	12.2	15.4	18.3
@ 40°C	ASTM D-445	34.8	109	155	202
Viscosity Index	ASTM D-2270	106	102	100	100
Flash Point COC°C	ASTM D-92	225	237	243	259
Pour Point °C	ASTM D-97	-27	-21	-21	-21
Sulphated Ash % w/w	ASTM D-874	0.91	0.91	0.91	0.91
TBN mg KOH/g	ASTM D-2896	7.1	7.1	7.1	7.1

### AVAILABLE IN

Bulk, 200 Litres, 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au). Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)"

**Effective:** October 2014

**Expires:** October 2016

EH410192/1



AUSTRALIAN FAMILY OWNED SINCE 1989

