



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362
5 Tarlington Place Smithfield NSW 2164
Correspondence: P.O Box 322 Castle Hill NSW 1765
Ph: 1300 796 009 | **Fax:** (02) 9604 1611 | **Email:** hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

HTO (PAO) SN/CF 10W60

DESCRIPTION

Hi-Tec HTO (PAO) SN/CF 10W60 is a full synthetic super high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection.

Hi-Tec HTO (PAO) SN/CF 10W60 is designed primarily for high performance and racing four stroke petrol engine in cars and motor cycles where the operator requires maximum protection and durability to obtain longer engine life.

Hi-Tec HTO (PAO) SN/CF 10W60 offers exceptional performance in the following areas:

- Superior high temperature stability
- Easier cold starting
- Lower oil consumption
- Much improved engine cleanliness

SPECIFICATIONS

Hi-Tec HTO (PAO) SN/CF 10W60 meets or exceeds the following demanding performance requirements:

API: SN, SM, SL, SJ, SH/ CF, CD, CE

TYPICAL TEST

	<u>Hi-Tec HTO (PAO) SN/CF 10W60</u>
Density, kg/lt @ 15 °C	0.851
Appearance	Fluoro
Viscosity, cSt @ 100 °C	23.0
cSt @ 40 °C	163
Viscosity Index	170
Flash Point, COC, °C	238
Pour Point, °C	-36
Carbon Residue, Conradson, % Mass	0.03
Foaming Characteristics, After Standing	Nil
Sulphated Ash, % wt	0.95
TBN, mg KOH/g	7.6
Zinc, % wt	0.08

Product Code: 2089

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes"

Effective: December 2012

Expires: December 2014

EH212102/6



AUSTRALIAN FAMILY OWNED SINCE 1989

