



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

PREMIER SL 20W/50

PRODUCT DESCRIPTION

Premier SL 20W/50 exceeds SL/CF rated performance, and is strongly recommended for all multi-valve and modern engines where a low temperature viscosity is required by the engine manufacturer for cold crank starts, but still providing protection in the summer heat.

Premier SL 20W/50 technology was formulated and developed through over twenty million kilometres of road testing around the world in vehicles of American, European and Japanese origin.

Premier SL 20W/50 is blended using only highly refined, virgin, paraffinic base stocks. The formulation of **Premier SL 20W/50** includes only materials of the highest quality.

Premier SL 20W/50 also meets the stringent shear stability (stay in grade) requirements of the CRC L38 and CCMC G4 specifications. The wide viscosity grade SAE 20W/50 provides the an ideal performance combination for Australia's climate: i.e. a low temperature viscosity permitting easy start-ups in winter, and high temperature viscosity providing superior performance and protection in the summer heat.

Always consult your vehicle owner's manual for the manufacturer's recommendations.

BENEFITS:

1. Engine cleanliness 60% cleaner than SF rated oils
2. Valve/Cam/Tappet wear reduced by half
3. High Temperature oil thickening reduced by 60%
4. Protects against rust and corrosion

SPECIFICATIONS

Premier SL 20W/50 is recommended for use in LRP (Super), Unleaded, L.P.G., and Turbo vehicles, as well as normally aspirated and Turbo-charged light diesels.

Premier SL 20W/50 meets and exceeds the following demanding performance requirements:

API: SL, SJ, SH/CF, CF, CD, EC

Japanese (JASO SE) Valve Train Wear Performance,

JASO MA



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TEST

ASTM METHOD

TYPICAL SAE 20W/50

Appearance	Visual	Natural
Density Kg/Lt at 15°C	D.1298	0.894
Viscosity, cSt at 40°C	D.445	187
at 100°C	D.445	19
Viscosity Index	D.2270	115
Flash Point, COC, °C	D.92	235
Pour Point, °C	D.97	-23
Foaming Characteristics -	D.892	Nil

Item Code: HI1-2043

AVAILABLE IN: Bulk, 200Litres, 20Litres, 5Litres

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes".

Effective: October 2014

Expires: October 2016

GH410192/1



AUSTRALIAN FAMILY OWNED SINCE 1989

