



## PRODUCT DATA SHEET

### SUPER HIGH PERFORMANCE SL/CF 20W/50

#### PRODUCT DESCRIPTION

**Hi-Tec Super High Performance SL 20W/50** engine oil is the ultimate in protection and performance. This premium quality engine oil is a complex blend of base oils and chemical additives designed to protect the engine and enhance its performance under extreme operating conditions such as high temperature motorway driving or low temperature stop and go driving.

**Hi-Tec Super High Performance SL 20W/50** contains detergents which neutralise the waste products from fuel combustion and prevent the formation of sludge and high temperature varnish deposits on critical engine components. Pistons stay clean and piston rings are prevented from gumming up. As well, anti-corrosion and anti-wear additives provide vital protection and minimise wear especially on cam shafts and valve gear.

**Hi-Tec Super High Performance SL 20W/50** exceeds the API SL/CF specifications and is suitable for high revving engines in High Performance Vehicles, 4 Stroke Motorcycles, LPG, Super, Unleaded, and Turbo Charged engines, as well as light diesels (both normally aspirated and turbo charged).

#### SPECIFICATIONS

**Hi-Tec Super High Performance SL 20W/50** meets the following demanding performance requirements:

API: SL, SJ, SH; CF, CD,

Ford M2C.153E

Always consult your vehicles owner's manual for the manufacturer's recommendations.

#### TYPICAL TEST

<u>TYPICAL TEST</u>	<u>ASTM METHOD</u>	<u>SHP 20W/50</u>
Appearance	Visual	Natural
Density Kg/Lt at 15°C	D.1298	0.894
Viscosity, cSt at 40°C	D.445	186
at 100°C	D.445	19.0
Viscosity Index	D.2270	115
Pour Point, °C	D.97	-23
Foaming Characteristics - All sequences after standing	D.892	Nil

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au). Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)"

Effective: October 2014

Expires: October 2016

GH410192/1

Product code: HI1-2044

Available in: Bulk, 200Litres, 20Litres, 5Litres

