



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

SYNPLUS A5/B5 5W30

DESCRIPTION

Hi-Tec Synplus A5/B5 5W30 is a full synthetic, full SAPS, super high performance engine oil which meets the ACEA A1/B1, ACEA A5/B5 and Ford WSS-M2C-913D specifications. It combines the latest developments in oil formulation and additive technology to provide a lubricating oil with the highest level of protection, whilst promoting fuel efficiency and lowering emissions in modern low friction engines.

Hi-Tec Synplus A5/B5 5W30 is intended for use at extended drain intervals in gasoline engines and car and light van diesel engines. These engines will be designed to be capable of using this low friction low viscosity oil with a High Temperature / High Shear Rate (HTHS) viscosity of between 2.9 and 3.5 mPa.s.

Hi-Tec Synplus A5/B5 5W30 meets the 2010 edition of the ACEA specifications in that it has improved sludge handling performance to further increase it's the long drain capabilities.

Hi-Tec Synplus A5/B5 5W30 meets the Ford WSS-M2C-913D specification, which defines a fuel economy engine oil suitable for many new Ford vehicles and is matched to the ACEA A5/B5 specifications. It is backwardly compatible with Ford WSS-M2C-913C, WSS-M2C-913B and WSS-M2C-913 specifications and can be used in cars requiring these engine oils.

Today's environmentally conscious market demands reduced emissions and increased fuel efficiency. Car manufacturers have developed smaller, higher output engines to meet these stricter requirements. These new engine designs have resulted in the need for higher performing lubricants.

Smaller engines help decrease vehicle weight and improve fuel economy but impact lubricants through:

- **Increased heat generation** which accelerates the rate of oil oxidation, nitration and deposit formation. This degrades the oil and encourages the creation of more acid and engine sludge and increases oil viscosity, resulting in more internal engine drag and less performance.

- **Increased internal pressures and engine speeds** which make it harder for the oil to maintain a lubricant film and prevent metal on metal contact. This accelerates valve train wear.

Hi-Tec Synplus A5/B5 5W30 is designed to meet these challenges to the engine's lubrication systems, providing full engine protection whilst increasing fuel economy and drain intervals and lowering emissions.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

SPECIFICATIONS

Hi-Tec Synplus A5/B5 5W30 meets:

ACEA:	A5/B5-10 A1/B1-10
API:	SL/CF
Ford:	WSS-M2C-913D, WSS-M2C-913C, WSS-M2C-913B, WSS-M2C-913
Renault:	RN0700

This oil is not suitable for all vehicles. Consult owner's manual or handbook if in doubt.

TYPICAL PROPERTIES

<u>PROPERTY</u>	<u>RESULT</u>
Density, kg/ltr @15°C	0.857
Viscosity, cSt @100°C	9.39
cSt @ 40°C	50.3
Viscosity Index	173
Total Base Number, mg KOH/g	11.2
Sulphated Ash, % wt	1.26
Calcium Content, % wt	0.325
Zinc Content, % wt	0.102
Phosphorus Content, % wt	0.095
Sulphur Content, % wt	0.265
Flash Point, °C min	200
Colour	Amber

Item Code: HI1-2112

Available In: Bulk, 200 Lt, 20 Lt, and 5 Lt

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes"

Effective: July 2014

Expires: July 2016

GH417052/1



AUSTRALIAN FAMILY OWNED SINCE 1989

