



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

BIO-HYDRAULIC OILS V TYPE

Hi-Tec Bio-Hydraulic Oils V Type are biodegradable ISO grade hydraulic lubricants containing vegetable oil based esters and high performance additive packages. They are designed to meet the requirements of ISO 15380:2002, are classified under ISO 6743-4 as Type HETG and are biodegradable according to OECD 301B.

Hi-Tec Bio-Hydraulic Oils V Type do not contain mineral lubricating oils: they are based on high quality vegetable oil esters, which in comparison with mineral oil based lubricants are more easily biodegraded, less hazardous and more suitable for use in environmentally sensitive areas. They are much less likely to cause any harm to soil, waterways or other parts of the environment than mineral oil based lubricants.

Hi-Tec Bio-Hydraulic Oils V Type display excellent viscosity - temperature characteristics due to the high inherent viscosity index of vegetable oil esters. Their optimum operating temperature range is from -10°C to 65°C.

Compared with mineral oil based lubricants **Hi-Tec Bio-Hydraulic Oils V Type** are:

- Safer for users and the environment
- More easily biodegradable
- Lower in toxicity – free from heavy metals
- Enhanced in performance characteristics
- Less changeable in viscosity as operating temperatures increase due to higher viscosity index
- Higher in lubricity resulting in lower equipment operating temperatures

Hi-Tec Bio-Hydraulic Oils V Type were developed to meet and exceed the current requirements of the agricultural, forestry, heavy engineering, construction and marine equipment industries.

Hi-Tec Bio-Hydraulic Oils V Type can be used in mobile or stationary equipment such as forklifts, cranes, tractors, graders, bulldozers, hoists, marine equipment, mining equipment, ski lifts etc. and are particularly suited to use in environmentally sensitive areas such as;

- National or State parks
- Near or on waterways
- Recreational areas
- Road, rail and tramways
- Local Government Maintenance Vehicles
- Water, Electricity, Telecommunication and Gas Service providers etc.

Hi-Tec suggests that the equipment manufacturers' recommendations for viscosity grade, performance requirements and general operating conditions should be checked prior to use.

Hi-Tec Bio-Hydraulic Oils V Type are fully miscible and compatible with mineral oils therefore changing to **Hi-Tec Bio-Hydraulic Oils V Type** is simple as no prior system flushing is required.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Hi-Tec Bio-Hydraulic Oils V Type contain ester components which may be incompatible with certain elastomers used as seals, hoses or other components. Prior to full scale commercial use it is recommended that compatibility with system components is determined by the user. For further advice contact your local reseller or supplier.

Avoid contamination with water. Where possible drying equipment should be used and water drained after any shutdown period.

TYPICAL CHEMICAL AND PHYSICAL CHARACTERISTICS

Properties	Unit	Test Method	ISO 32	ISO 46	ISO 68
Appearance	-	Visual	Clear yellow liquid		
Odour	-	-	Bland fatty		
Density @ 15°C	kg/L	ASTM D4052	0.92		
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D445	32	46	68
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D445	7.6	9.9	13.2
Viscosity Index	-	ASTM D2270	220	210	200
Pour Point	°C	ASTM D97	-15		
Flash Point Open Cup	°C	ASTM D92	>150		
Corrosiveness to Copper	-	ASTM D130	1a		
Rust Preventing Characteristics	-	ASTM D665	Pass A & B		
Sulphated Ash	%m/m	ASTM D874	0.01		
Water Content	%v/m	ASTM D95	<0.1		

Available in: 200Litres, 20Litres, 5Litres, 1Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au.

Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: August 2014

Expires: August 2016

GH418070/1



AUSTRALIAN FAMILY OWNED SINCE 1989

