



Correspondence: P.O Box 322 Castle Hill NSW 1765

**Ph:** 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## MATERIAL SAFETY DATA SHEET

Page 1 of 9

Issue Date: 1st February 2012 Calcium Sulphonate Grease

Version: 1

**Product name: Calcium Sulphonate Grease** 

### 1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)

ADDRESS: PO Box 322 Castle Hill NSW 1765

5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: Calcium Sulphonate Grease

OTHER NAMES: None

MANUFACTURER'S PRODUCT CODE: HI7-1025

USE: Calcium sulphonate complex grease for automotive and industrial

applications

Refer to Product Information Sheet for additional information. ADDITIONAL INFORMATION:

OTHER INFORMATION: Visit our website: www.hi-tecoils.com.au

Email: hitecoils@hi-tecoils.com.au

#### 2. HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: NON-HAZARDOUS SUBSTANCE

**NON-DANGEROUS GOODS** 

Hazard classification according to criteria of NOHSC.

Dangerous goods classification according to Australian Dangerous Goods

Code.

RISK PHRASE (S):

**IRRITANCY OF PRODUCT:** Not classified as an irritant.

SENSITISATION OF PRODUCT: Not known to be a sensitiser.

TERATOGENICITY: No teratogenic effects known.

Hi-Tec Oils (QLD) 78 Nestor Drive **MEADOWBROOK** QLD 4131 Ph: (07) 3200 3492 Fx: (07) 3200 7136 Hi-Tec Oils (VIC) 1 Venture Drive SUNSHINE WEST VIC 3020 Ph: (03) 9314 2524 Fx: (03) 9314 2676 Hi-Tec Oils (TAS) Authorised Distributor **Duo Trading** Ph: (03) 6278 1616

Hi-Tec Oils (ACT) Superlube Distributors PH: (02) 6232 9515

Hi-Tec Oils (SA) 3A Unit 6 & 7 Newcastle Cres CAVAN SA 5094 PH: (08) 8162 5807 FX: (08) 8359 7849

Hi-Tec Oils (WA) Unit 1, 2 Cutting Way Yangebup WA 6164 PH: (08) 9418 5380 FX: (08) 9418 5380

Hi-Tec Oils (NT) 71 Marjorie Street Pinelands NT 0829 PH: (08) 8931 0229 FX: (08) 8932 6510







Correspondence: P.O Box 322 Castle Hill NSW 1765

**Ph:** 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## MATERIAL SAFETY DATA SHEET

Page 2 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

2. HAZARDS IDENTIFICATION (CONT.)

OTHER INFORMATION:

Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used oils should be

handled with caution and skin contact avoided as far as possible.

3. IDENTIFICATION / COMPOSITION OF INGREDIENTS

CHEMICAL CHARACTERISTICS: Grease

INGREDIENTS:-

CHEMICAL ENTITY: CAS No. PROPORTION
Lubricating Oils, Petroleum, Base Oils, highly refined Overbased Calcium Sulfonate Complex Thickener Confidential 15% < 30%
Ingredients determined not to be hazardous Mixture To 100%

OTHER INFORMATION:

Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used oils should be handled with caution and skin contact avoided as far as possible.

### 4. FIRST AID MEASURES

**HEALTH EFFECTS** 

SWALLOWED: Ingestion of small quantities should not cause irritation, but may cause diarrhoea. If a large

quantity is ingested seek immediate medical attention. Give water to drink. DO NOT induce vomiting. If vomiting occurs get immediate medical attention due to aspiration into lungs

risk. Not expected to be toxic by ingestion.

EYE: May cause irritation to the eyes. Immediately irrigate with copious amounts of water for at

least 15 minutes. Eyelids to be held open. In all cases of eye contamination it is a sensible

precaution to seek medical advice.

SKIN: May be irritating to the skin. Remove contaminated clothing and wash skin thoroughly with

plenty of soap and water. High pressure injection through the skin requires **URGENT** medical attention for possible incision, irrigation and/or debridement. Contact with molten

material will require treatment by a physician for burns (Do not remove material).







Correspondence: P.O Box 322 Castle Hill NSW 1765 **Ph:** 1300 796 009 | 61 2 9616-5700 (Int')

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

# **MATERIAL SAFETY DATA SHEET**

Page 3 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

### 4. FIRST AID MEASURES (CONT.)

INHALED: No data to indicate a toxic inhalation hazard. Inhalation of vapours or mist (generated at

elevated temperatures) may cause irritation to the nose and throat, and there may be delayed onset of pulmonary oedema or pneumonia if aspirated. Remove victim from exposure to fresh air – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through face mask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage and seek urgent medical aid.

FIRST AID FACILITIES: Normal washroom facilities are generally suitable. Ensure an eye wash station and safety

shower is available and ready for use

ADVICE TO DOCTOR: Treat symptomatically.

OTHER INFORMATION: Keep water and mild soap near work site.

#### 5. FIRE FIGHTING MEASURES

#### FIRE/EXPLOSION HAZARD

HAZARDS OF USE/STORAGE: Product is a C2 combustible solid according to AS 1940. This product is

combustible if preheated.

HAZARDS FROM COMBUSTION PRODUCTS: Combustion products may include: oxides of carbon, calcium and sulphur,

a complex mixture of airborne unidentified organic and inorganic solid and

liquid particulates.

FIRE-FIGHTING RECOMMENDATIONS: If safe to so, remove containers from path of fire. Keep storage tanks,

pipelines, containers, fire exposed surfaces, etc. cool with water spray.

Avoid spreading liquid and fire by water flooding.

PRECAUTION: Water may cause splattering.

SUITABLE EXTINGUISHING MEDIA: Use foam, water fog, carbon dioxide, dry sand or dry chemical.

PROTECTIVE MEASURES: Fire fighters should wear self-contained breathing apparatus if risk of

exposure to products of combustion.

REACTIVITY: May react with strong acids and oxidising agents.

PH: (02) 6232 9515







Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## **MATERIAL SAFETY DATA SHEET**

Page 4 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

#### 6. ACCIDENTAL RELEASE MEASURES

SPILLS & DISPOSAL: Slippery when spilt. Avoid accidents, clean up immediately.

CLEAN-UP PROCEDURE - SMALL SPILLS (20L or less): Absorb or contain liquid with sand, earth or spill control material. Shovel up using non-sparking tools and place in a sound labelled sealable container for subsequent safe disposal. Place leaking containers in a sound labelled drum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste.

CLEAN-UP PROCEDURES - LARGE SPILLS (Greater than 20L): Transfer to a sound labelled, sealable container for product recovery or safe disposal. Treat residues as for small spills.

PERSONAL PRECAUTIONS: Extinguish naked flames. Remove ignition sources. No smoking. Avoid sparks. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Evacuate the area of non-essential personnel. Shut off leaks, if possible without personal risk. Do not breathe vapours. Ventilate contaminated area thoroughly. Dispose of according to local regulations.

OTHER INFORMATION:

PROCEDURES IN CASES OF LEAKAGE OR BREAKAGE: Stop the source of the leak or release and contain spill if possible. Ventilate area. Use respirator and protective clothing outlined in this MSDS. Cover spill with inert absorbent earth. Use a stiff brush to mix thoroughly. Sweep up and place in a sound labelled disposable container. Scrub contaminated area with detergent and water using a stiff brush. Pick up liquid with additional absorbent material and place in a sound labelled disposable container. Prevent contamination of groundwater or surface water.

#### 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: When handling product in drums, safety footwear should be worn and proper

handling equipment should be used. Prevent spillages. Ensure the appropriate personal protective equipment is used when handling this product. Ensure high level of personal hygiene is maintained when using this product. That is; always

wash hands before eating, drinking smoking or using the toilet.

SAFE STORAGE CONDITIONS: Keep containers closed at all times. Store in a cool place out of direct sunlight.

Store away from oxidising agents. Check containers regularly for leaks.

CORROSIVENESS: Not corrosive.







Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

# MATERIAL SAFETY DATA SHEET

Page 5 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

### 7. HANDLING AND STORAGE (CONT.)

STORAGE REGULATIONS: Store in a well ventilated place away from ignition sources, oxidising agents,

foodstuffs and clothing.

Keep containers closed when not in use.

Refer to AS 1940 – The Storage and Handling of Flammable Liquids, and NOHSC: 1015 – National Standard for Storage and Handling of Workplace

Dangerous Goods for further information.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

NATIONAL EXPOSURE STANDARDS: No exposure standard has been established for this product. NOHSC Exposure

Standard: Oil mists – time weighted average (TWA) 5 mg/m<sup>3</sup> is recommended.

OTHER EXPOSURE INFORMATION: Exposure Standard means the average concentration of a particular substance in the

worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term

exposure limit (STEL).

ENGINEERING CONTROLS: Maintain concentration below recommended exposure limit. Special ventilation is

not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the exposure

standard or the Manufacturer's recommended exposure standard.

RESPIRATORY PROTECTION: A respirator is not normally required. Airborne concentrations should be kept at

lowest level possible. If vapours, mists or dusts are generated and the recommended exposure limit for the product is exceeded, use appropriate AS/NZS 1715/1716 approved half—face filter respirator suitable for organic vapours or air supplied respirator are worn. Air supplied respirators should always be worn when the airborne concentration of the contaminant or the oxygen content of the air is

unknown

EYE PROTECTION: Safety glasses, goggles or face shield as appropriate.

HAND PROTECTION: PVC gloves.

FOOTWEAR: Enclosed footwear.

BODY PROTECTION: Overalls or similar protective apparel.







5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

**Ph:** 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## **MATERIAL SAFETY DATA SHEET**

Page 6 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT)

HYGIENE MEASURES: Always wash hands before eating, drinking, smoking or using the toilet. If

contamination occurs, change clothing. Launder contaminated clothing before

reuse. Discard internally contaminated gloves.

SPECIAL PROTECTIVE MEASURES: The product will not burn unless preheated. Isolate from sources of heat, naked

flames or sparks.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Grease

APPEARANCE: Smooth.

COLOUR: Tan

ODOUR: Mild petroleum

DROP POINT: 318°C

BOILING POINT: Not distillable

DENSITY @  $25^{\circ}$ C (kg/L): 0.95 - 1.05

FLASHPOINT (ASTM D-93), Closed Cup: >180°C

FLAMMABILITY LIMITS -LOWER: Not available

FLAMMABILITY LIMITS -UPPER: Not available

FLAMMABILITY: Combustible Solid C2 according to AS 1940.

SOLUBILITY IN WATER: Negligible.

SOLUBILITY IN ORGANIC SOLVENTS: Partially soluble.

VAPOUR PRESSURE: <0.1mm Hg

VAPOUR DENSITY (Air = 1): Not available

NLGI Grade: 2







Correspondence: P.O Box 322 Castle Hill NSW 1765

**Ph:** 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## **MATERIAL SAFETY DATA SHEET**

Page 7 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

### 9. PHYSICAL AND CHEMICAL PROPERTIES (CONT)

EVAPORATION RATE: Less than 1 (n-butyl acetate = 1)

AUTO-IGNITION TEMPERATURE: Not available

EXPLOSION PROPERTIES: Not considered an explosion risk under normal conditions of use.

OTHER INFORMATION: These physical data and other properties do not constitute a specification.

### 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under normal conditions of use.

CONDITIONS TO AVOID: Heat, direct sunlight, open flames or other sources of ignition.

INCOMPATIBLE MATERIALS: Strong oxidising agents.

HAZARDOUS REACTIONS: Will react with strong oxidising agents.

HAZARDOUS POLYMERISTION: Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

TOXICOLOGY INFORMATION: This product contains petroleum base oils, which may be refined by various

processes including severe solvent extraction, hydro cracking and hydro treating. These oils have not been listed in the U.S. National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic or probably carcinogenic to humans.

Oral LD50 ({UDO1}): { UDO2} mg/kg.

ORAL TOXICITY (RATS): Based upon testing of similar products and/or components, this material is

considered to be relatively non-toxic with a LD50: > 2000 mg/Kg.

DERMAL TOXICITY (RABBITS): Based upon testing of similar products and/or components, this material is

considered to be relatively non-toxic with a LD50: > 2000 mg/Kg.

EYE IRRITATION (RABBITS): Based upon testing of similar products and/or components, this material is

considered to be relatively non-irritating with a Draize Score: Greater than 6, but

less than 15.

SKIN IRRITATION (RABBITS): Based upon testing of similar products and/or components, this material is

considered to be relatively non-irritating with a Primary Irritation Index: Greater

than 0.5, but less than 3.

SUBCHRONIC TOXICITY (RATS): Based upon testing of similar products and/or components, this material is

considered to show no adverse effects by dermal application to rats.







Correspondence: P.O Box 322 Castle Hill NSW 1765

**Ph:** 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## MATERIAL SAFETY DATA SHEET

Page 8 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

11. TOXICOLOGICAL INFORMATION (CONT.)

REPRODUCTIVE TOXICITY (RATS): Based upon testing of similar products and/or components, this material is

considered to show no adverse effects in either the mothers or their offspring by

dermal exposure of pregnant rats.

CHRONIC TOXICITY (MICE): Based upon testing of similar products and/or components, this material is

considered to show no evidence of carcinogenic effects by chronic mouse skin

painting studies.

SENSITISATION (GUINEA PIGS): Based upon testing of similar products and/or components, this material is

considered to show no evidence of skin sensitisation to guinea pigs during studies.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Leaching and penetration through soils is generally regarded as resulting in long-

term persistence. Fresh or used product may be harmful to aquatic life.

Do not allow material to enter drains or watercourses. This product is stable in water, and can be mechanically separated from the water. The water may be suitable

for disposal in a biological waste water treatment plant.

13. DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATIONS: Dispose of according to federal, E.P.A. and state regulations.

14. TRANSPORT INFORMATION

TRANSPORT INFORMATION: Not classified as a Dangerous Good according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail.

15. REGULATORY INFORMATION

POISON SCHEDULE: Not scheduled.

PACKING & LABELLING: No special packaging or labelling requirements.

AUSTRALIAN INVENTORY STATUS: All components are listed or exempted.







Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | 61 2 9616-5700 (Int'l)

Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

## **MATERIAL SAFETY DATA SHEET**

Page 9 of 9

Issue Date: 1<sup>st</sup> February 2012 Calcium Sulphonate Grease

Version: 1

#### 16. OTHER INFORMATION

CONTACT PERSON/POINT: General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Material Safety Data Sheets are updated frequently. Please ensure you have a current copy.

#### LITERATURE REFERENCES:

- \* NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
- \* NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
- \* NOHSC: 10005 List of Designated Hazardous Substances.
- \* NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
- \* NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
- \* NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
- \* NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
- \* NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
- \* NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice
- \* SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
- \* ADG: Australian Dangerous Goods Code
- \* MSDS of component materials.

LAST CHANGE:

Supersedes document issued: New

Reason/s for revision: Alignment to NOHSC requirements.

GH212010/2

**END OF MSDS** 

