



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

DIESEL FUEL TREATMENT

Description & Application:

Diesel Fuel Treatment is a multifunctional diesel fuel maintenance additive. It is specifically designed to give an overall improvement on most aspects of fuel efficiency. It provides several benefits to users as follows:

1. Injector Cleanliness
2. Improved exhaust emission
3. Powerful biocide
4. Improves fuel economy
5. Improves lubricity
6. Enhances fuel stability
7. Enhances demulsibility

The recommended treat rate is 1:500 for the initial first time treatment and 1:1000 to 1:2000 for subsequent treatments. Add the required amount of Diesel Fuel Treatment to the tank prior to filling tank with diesel fuel.

This product has a shelf life of two years from date of manufacture.

Typical Properties

Appearance	Light brown coloured liquid
Transparency	Clear
Density, kg/l	0.82 +/- 0.02

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Available in: 205 Litres, 20 Litres, 5 Litres and 1 Litre

Item Code: HI8-3120-
Effective: Sept 2014
Expires: Sept 2016
EH410120/1



AUSTRALIAN FAMILY OWNED SINCE 1989

