

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

FAST 2 HIGH PERFORMANCE 2 STROKE

PRODUCT DESCRIPTION

Hi-Tec Fast 2 High Performance 2 Stroke is designed to be used in high performance top tier two stroke motor cycle engines and power tools. It is formulated from a high quality mineral base stock with detergent additives to create a modern low ash lubricant.

Hi-Tec Fast 2 High Performance 2 Stroke has consistently given excellent engine cleanliness and freedom from ring sticking under controlled test conditions. Its performance reputation is based upon practical field experience involving the continual development and improvement of the lubricant additive system in high performance motorcycle racing engines.

Hi-Tec Fast 2 High Performance 2 Stroke is manufactured with self-mixing solvents and should be used at the fuel/oil ratio recommended by the engine manufacturer.

Hi-Tec Fast 2 High Performance 2 Stroke may also be used in small to medium sized water-cooled engines, which may not be sensitive to low ash levels. However it should not be used in water-cooled outboard engines.

Hi-Tec Fast 2 High Performance 2 Stroke meets the requirements of the JASO FA and FB, ISO-L-EGB and API TC specifications.

PROPERTY	ASTM METHOD	TYPICAL
Density, kg/Lt @ 15.0°C	ASTM D.1298	0.868
Viscosity cSt @ 40°C	ASTM D.445	50
Nitrogen Content, %wt	ASTM D.3228	0.02
Calcium Content, %wt	ASTM D.4927	0.04
Ash, % wt	ASTM D-874	0.14

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes".

Product Code: 2135A

Effective: February 2015 February 2017 Expires:

MH513060/1





