



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

FAST 2 SYNTHETIC 2 STROKE

DESCRIPTION

Hi-Tec Fast 2 Synthetic 2 Stroke is a premium fully synthetic low ash, low smoke two-stroke lubricant formulated with specially developed diester basestock for superior lubricity and performance.

Hi-Tec Fast 2 Synthetic 2 Stroke is blended to meet the severe high temperature and high load requirements of modern two-stroke engines. It has excellent low temperature properties for use under extreme temperature conditions.

Hi-Tec Fast 2 Synthetic 2 Stroke provides superior balanced performance exceeding the requirements for the American API TC standard, the European ISO-L-EGD and ISO-L-EGC standards, and the Japanese JASO FD and FC standards. It exceeds the requirements of the Thai Industrial Standards Institute (TISI) for use in Thailand

Hi-Tec Fast 2 Synthetic 2 Stroke performs extremely well in Go-Kart Racing. It allows an increase in fuel/oil ratio and the engines remain very clean and are able to be reused.

SERVICE RECOMMENDATIONS

Hi-Tec Fast 2 Synthetic 2 Stroke is particularly recommended for use in high performance air-cooled two stroke engines, such as those used for road and racing motor cycles, go-karting, snowmobiles and chainsaws; as well as highly rated water cooled two stoke engines.

Hi-Tec Fast 2 Synthetic 2 Stroke meets and exceeds the following performance levels:

- API TC
- ISO-L-EGB, -EGC and -EGD
- JASO FA, FB, FC and FD
- TISI requirements for Detergency and Lubricity
- Piaggio Hexagon

It is recommended for use in:

- HUSQVARNA Chainsaws
- ROTAX Snowmobiles



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL TESTS	ASTM METHOD	SYN 2T
Appearance	Visual	Blue
Density, kg/Lt at 15.0°C	D.1298	0.885
Viscosity, cSt at 40°C	D.445	57.1
at 100°C	D.445	9.46
Ash, Sulphated, %	D.874	0.36
Pour Point, °C	D.97	-57
Brookfield Viscosity @ -25°C, cP	D.5133	5410
Brookfield Viscosity @ -40°C, cP	D.5133	37400
Flash Point, PM, °C	D.93	70
Nitrogen Content, %wt	D.3228	0.06
Calcium Content, %wt	D.4927	0.11

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes".

Product Code: 2134A

Effective: July 2012

Expires: July 2014

EH217081/1



AUSTRALIAN FAMILY OWNED SINCE 1989

