



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

FAST 4 SN MA 10W40 SEMI SYN

PRODUCT DESCRIPTION

Hi-Tec Fast 4 SN MA 10W40 Semi Syn exceeds the JASO MA specification requirements for use in four stroke motorcycles with wet clutches. This specification ensures that this oil has the correct friction requirements with respect to the Dynamic Friction Index (DFI), the Static Friction Index (SFI) and the Stop Time Index (STI) allowing “wet clutches” in four stroke motor bikes to hold and release at the correct time and speed to allow accurate and predictable gear changes.

Hi-Tec Fast 4 SN MA 10W40 Semi Syn also exceeds API SN performance requirements, and is strongly recommended for multi-valve and four stroke engines where a low temperature viscosity is required by the engine manufacturer for cold crank starts, but still providing protection in the summer heat.

Hi-Tec Fast 4 SN MA 10W40 Semi Syn is strongly recommended for multi-valve and four stroke engines where a low temperature viscosity is required by the engine manufacturer for cold crank starts, but still providing protection in the summer heat.

Hi-Tec Fast 4 SN MA 10W40 Semi Syn technology was formulated and developed through over twenty million kilometres of road testing around the world in vehicles of American, European and Japanese origin.

Hi-Tec Fast 4 SN MA 10W40 Semi Syn is blended using only highly refined, synthetic technology paraffinic base stocks and high performance additive systems to ensure engine performance, cleanliness and reliability.

Always consult the vehicle owner’s manual for the manufacturer’s recommendations.

BENEFITS:

- Piston deposits reduced by 14% over SM rated oils
- Engine sludge reduced by 2.5%
- E85 compatible
- Protects against rust and corrosion

SPECIFICATIONS

Hi-Tec Fast 4 SN MA 10W40 Semi Syn is recommended for use in four stroke motorcycle engines, and on and off road motor cycles, and contains additives suitable for integrated clutches and gearboxes.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Hi-Tec Fast 4 SN MA 10W40 Semi Syn meets and exceeds the following demanding performance requirements:

API SN, SM, SL, CF, CF, CD, CE

JASO MA

JASO SE Valve Train Wear Performance

Ford M2C. 153E

<u>TEST</u>	<u>ASTM METHOD</u>	<u>TYPICAL VALUE</u>
Appearance	Visual	Natural
Density Kg/Lt at 15°C	D.1298	0.872
Viscosity, cSt at 40°C	D.445	104
at 100°C	D.445	14.5
Viscosity Index	D.2270	144
Borderline Pumping, Pass °C	D.3829	-25
Flash Point, COC, °C	D.92	235
Pour Point, °C	D.97	-30
Total Base Number	D.2896	7.5
Foaming Characteristics	D.892	Nil

Available in: 200 Litres, 20 Litres, 5 Litres, 1 Litre

Item Code: HI1-2082A

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes".

Effective: July 2014

Expires: July 2016

GH417041/1



AUSTRALIAN FAMILY OWNED SINCE 1989

