



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362
5 Tarlington Place Smithfield NSW 2164
Correspondence: P.O Box 322 Castle Hill NSW 1765
Ph: 1300 796 009 | **Fax:** (02) 9604 1611 | **Email:** hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

HD HAMMER CHISEL PASTE

DESCRIPTION

Hi-Tec HD HAMMER CHISEL PASTE is a grease formulated to provide lubrication of hydraulic hammers and is fortified with solids to prevent galling and seizing. It has an operating temperature range of -30 to +200°C with protection up to 1000°C provided by the solids content.

TYPICAL TESTS

	<u>ASTM</u>	<u>VALUE</u>
NLGI		2
Appearance		Copper / Gray
Gelling Agent		Calcium Sulphonate Complex
Penetration, Worked @ 25 °C	D.217	250 – 290
After 10,000, % change		+/- 5
Dropping Point, min °C	D.2265	260
Solids, graphite and copper %		14
4-Ball Weld, kg	D.2596	800
4-Ball Wear, Scar Diameter, mm	D.2266	0.60
Rust Prevention Characteristics	D.1743	Pass
Mineral Oil, Viscosity, cSt @ 40°C	D.445	200 - 240
@ 100°C	D.445	18 - 20

Product Code: HI7-1035-

"The facts stated and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes."

Effective: August 2013
Expires: August 2015
GH318080/1



AUSTRALIAN FAMILY OWNED SINCE 1989

