

 Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362
 5

 5 Tarlington Place Smithfield NSW 2164
 6

 Correspondence: P.O Box 322 Castle Hill NSW 1765
 7

 Ph: 1300 796 009 | 61 2 9616-5700 (Int'l)
 6

 Fax: 61 2 9604-1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

Page 1 of 6 Issue Date: 1st March 2011 Nevermelt Grease Version 1

MATERIAL SAFETY DATA SHEET

Product name:

Nevermelt Grease

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: ADDRESS:

TELEPHONE NUMBER: FAX NUMBER:

PRODUCT NAME: OTHER NAMES: MANUFACTURER'S PRODUCT CODE: USE Hi-Tec Oil Traders Pty Ltd. Po Box 322 Castle Hill NSW 1765 5 Tarlington Place, Smithfield NSW 2164 1300 796 009 (02) 9604 1611

Nevermelt Grease None HI7-1008-Clay thickened multipurpose high temperature grease

2. STATEMENT OF HAZARDOUS NATURE

This product is classified as NON HAZARDOUS according to NOHSC criteria. Non Dangerous goods according to Australian Dangerous Goods Code.

3. IDENTIFICATION / COMPOSITION OF INGREDIENTS

INGREDIENTS

CHEMICAL ENTITY: CAS No. PROPORTION 64742-62-7 Residual Oils(Petroleum), Solvent Dewaxed > 60% Organic Modified Clay(Organophilic Clay) 68953-58-2 < 10% 1,2,3-Propanetriol(Glycerol Anhydrous) 56-81-5 < 10% Zinc Diamyldithiocarbamate 15337-18-5 < 10% Tri-Sodium Phosphate Anhydrous 7601-54-9 < 10%

4. FIRST AID MEASURES / HEALTH HAZARD INFORMATION

HEALTH EFFECTS

SWALLOWED:	This is not expected to be a means of entry during routine operation.
	Ingestion of small quantities should not cause irritation.
EYE:	May cause slight irritation to the eyes.
SKIN:	May be mildly irritating to the skin. High pressure injection
	EYE:

Page 1 of 6 – Material Safety Data Sheet - Nevermelt Grease - Issue Date: 1st March 2011 Version 1

4. FIRST AID MEASURES / HEALTH HAZARD INFORMATION (CONT.)

	INHALED:	through the skin, when using apparatus such as grease guns, can be highly irriating and may cause localised damage. No data to indicate a toxic inhalation hazard. Inhalation of vapours or mist (generated at elevated temperatures) may cause irritation to the nose and throat.
CHRONIC:		Prolonged or repeated skin contact may lead to drying of the skin.
FIRST AID	SWALLOWED:	If a large quantity is ingested seek medical attention. It may be necessary to induce vomiting, taking extreme care that the person does not aspirate into the lungs. If aspiration occurs, urgent medical attention should be sought.
	EYE:	Wash with copious amounts of water for 15 minutes and seek medical advice if irritation develops or persists.
	SKIN:	Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. High pressure injection through the skin requires urgent medical attention for possible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns (Do not remove material).
	INHALED:	Remove person to fresh air and seek medical advice. If not breathing, apply artificial respiration and seek urgent medical aid.
	FIRST AID FACILITIES:	Eye wash fountains and safety showers are recommended.
ADVICE TO D	OCTOR:	Treat symptomatically.

5. FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

HAZARDS OF USE/STORAGE: LIST OF DANGEROUS DECOMPOSITION OR COMBUSTION PRODUCTS: FIRE-FIGHTING RECOMMENDATIONS:

TYPES OF EXTINGUISHER/ FIRE-FIGHTING AGENTS: PRECAUTION: PROTECTIVE CLOTHING: REACTIVITY: This product is combustible if heated.

Combustion produces oxides of carbon, nitrogen and sulphur. Keep storage tanks, pipelines, containers, fire exposed surfaces, etc. cool with water spray.

Use foam, carbon dioxide or dry chemical. Water may cause splattering. Self-contained breathing apparatus is recommended during a fire. May react with strong oxidising agents.

6. ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimize exposure. If possible, contain the spill. Place inert, non-combustible, absorbent material onto the spillage. Use clean, non-sparking tools to collect the material and place into a suitable labelled container. If large

Page 2 of 6 - Material Safety Data Sheet - Nevermelt Grease - Issue Date: 1st March 2011 Version 1

quantities of this material enter the waterways, contact the Environmental Protection Authority, or your local Waste Water Authority.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:	Repeated or prolonged contact with this material should be avoided in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene, i.e. washing hands prior to eating, drinking or going to the toilet. Build-up of mists or vapours in the working environment must be prevented.
STORAGE AND TRANSPORT:	Classified as a combustible solid. Store in a well ventilated area away from ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Do not store in plastic containers unless approved for this application.
SPILLS AND DISPOSAL:	Spills are easily contained due to the nature of the product. Caution: The product may be slippery. The product should be shovelled into a metal drum and treated as a solid waste. Follow state or local regulations for the disposal of the waste. Clean area with soap and water. Do not allow product to enter drains, sewers or water courses – inform local authorities if this occurs.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE STANDARDS:	If the material is subjected to high temperature operations and mists or vapours are generated the Manufacturer recommends: Time Weighted Average (TWA): 5 mg/m ³ (oil mist). Short Term Exposure Limit (STEL): 10 mg/m ³ (oil mist).
ENGINEERING CONTROLS:	Special ventilation is not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the Manufacturer recommended exposure standard.
PERSONAL PROTECTION	
RESPIRATOR TYPE (AS1716):	During routine operation a respirator is not required. However, if mists or vapours are generated, an approved organic vapour / particulate respirator is required.
GLOVE TYPE:	PVC, Neoprene or Nitrile gloves are recommended.
EYE PROTECTION:	Safety glasses or goggles are recommended to avoid eye contact. If the material is used at elevated temperatures or under pressure a full face shield should be worn.
CLOTHING:	During normal operating procedures, long sleeved clothing is recommended to

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL DESCRIPTION/PROPERTIES

APPEARANCE:	Smooth amber grease.
VAPOUR PRESSURE (Pa or mmHg at 20°C):	Not available.
DENSITY @ 15°C (g/mL):	Typically 0.90
FLASHPOINT(°C):	>200°C (ASTM D-93), Closed Cup.
FLAMMABILITY LIMITS (%):	Not available.
FLAMMABILITY:	Non Flammable, but combustible.
SOLUBILITY IN WATER (g/L) :	Not miscible

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under normal conditions.
CONDITIONS TO AVOID:	Heat, direct sunlight, open flames or other sources of ignition.
INCOMPATIBLE MATERIALS:	Strong oxidising agents.
HAZARDOUS DECOMPOSITION:	Thermal decomposition and combustion produce noxious fumes containing oxides of carbon, nitrogen and sulphur.
HAZARDOUS REACTIONS:	Hazardous reaction with strong oxidising agents.
HAZARDOUS POLYMERISTION:	Will not occur.

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA:

ORAL TOXICITY (RATS):Based upon testing of similar products and/or components, this material is considered
to be relatively non-toxic with a LD50: > 2000 mg/Kg.DERMAL TOXICITY (RABBITS):Based upon testing of similar products and/or components, this material is considered
to be relatively non-toxic with a LD50: > 2000 mg/Kg.

11. TOXICOLOGICAL INFORMATION (CONT)

EYE IRRITATION (RABBITS):	Based upon testing of similar products and/or components, this material is considered to be relatively non-irritating with a Draize Score: Greater than 6, but less than 15.
SKIN IRRITATION (RABBITS):	Based upon testing of similar products and/or components, this material is considered to be relatively non-irritating with a Primary Irritation Index: Greater than 0.5, but less than 3.
SUBCHRONIC TOXICITY (RATS):	Based upon testing of similar products and/or components, this material is considered to show no adverse effects by dermal application to rats.
REPRODUCTIVE TOXICITY (RATS):	Based upon testing of similar products and/or components, this material is considered to show no adverse effects in either the mothers or their offspring by dermal exposure of pregnant rats.
CHRONIC TOXICITY (MICE):	Based upon testing of similar products and/or components, this material is considered to show no evidence of carcinogenic effects by chronic mouse skin painting studies.
SENSITISATION (GUINEA PIGS):	Based upon testing of similar products and/or components, this material is considered to show no evidence of skin sensitisation to guinea pigs during studies.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No data available for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATIONS: Dispose of according to federal, E.P.A. and state regulations.

14. TRANSPORT INFORMATION

TRANSPORT INFORMATION: Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

15. CONTACT POINT

CONTACT PERSON/POINT: General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.
If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Page 6 of 6 - Material Safety Data Sheet - Nevermelt Grease - Issue Date: 1st March 2011 Version 1

15. CONTACT POINT (CONT)

	Material Safety Data Sheets are updated frequently. Please ensure you have a current copy.
LITERATURE REFERENCES:	 * NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets. * NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances. * NOHSC: 10005 List of Designated Hazardous Substances. * NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice. * NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice. * NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards. * NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note. * NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard. * NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice. * SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons * ADG: Australian Dangerous Goods Code * MSDS of component materials.
LAST CHANGE:	Supercedes document issued: May 2006 Reason/s for revision: Alignment to NOHSC requirements.
GH113010/1	

GH113010/1

END OF MSDS

This MSDS summarises Hi-Tec Oil Traders Pty Ltd best knowledge of the health and safety hazard information of the selected substance and how to safely handle the selected substance in the workplace however Hi-Tec Oil Traders Pty Ltd expressly disclaims that the MSDS is a representation or guarantee of the chemical specifications for the substance.

Each user should read the MSDS and consider the information in the context of how the selected substance will be handled and used in the workplace including its use in conjunction with other substances.

© Copyright 2011 Hi-Tec Oil Traders Pty Ltd