



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

# PRODUCT DATA SHEET

## RADIATOR TREATMENT

### PRODUCT DESCRIPTION

**Hi-Tec Radiator Treatment** is a general purpose automotive cooling system corrosion inhibitor concentrate. It is suitable for passenger cars and light commercial vehicles. It contains a mixture of highly efficient corrosion and rust inhibitors developed for the newest generation of modern vehicles.

**Hi-Tec Radiator Treatment** provides long-life corrosion protection for aluminium and ferrous alloys and is fully compatible with the rubber hoses and plastics used in engine cooling systems.

**Hi-Tec Radiator Treatment** exceeds the requirements of Australian/New Zealand standard AS/NZ 2108.1 (1997) Type B.

**Hi-Tec Radiator Treatment** contains no ethylene glycol. It is not an anti-freeze/anti-boil type coolant and should not be used in conflict with engine manufacturers' recommendations. It will not reverse pre-existing corrosion problems.

### APPLICATION

Use **Hi-Tec Radiator Treatment** at 40-50ml per litre in distilled water. If required, top up with diluted **Hi-Tec Radiator Treatment** to avoid a rundown in concentration.

Replace **Hi-Tec Radiator Treatment** at 24 month/40,000 kilometre intervals. It may be replaced more frequently depending on engine and driving conditions, or engine manufacturer's requirements.

To avoid possible incompatibility problems, do not mix **Hi-Tec Radiator Treatment** with any other inhibitors or coolants.

### DIRECTIONS FOR USE

When the vehicle engine is cool, drain the cooling system (including the heater) as per the vehicle owners handbook. Thoroughly flush and rinse the cooling system. Reconnect all hoses, drain plugs, etc; then fill the cooling system with the correct volume of water (as per the vehicle owners handbook), and add the appropriate dosage of **Hi-Tec Radiator Treatment**.

Check the level of the **Hi-Tec Radiator Treatment** and top up after running the engine to operating temperature and allowing it to cool again.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

# PRODUCT DATA SHEET

## PROPERTIES

Appearance:	Pale green
Specific Gravity (kg/l):	Typically 1.05 – 1.07
pH:	9.3 – 9.5
Flashpoint, Closed Cup:	Does not burn

**Item Code:** HI8-3400

**Available in:** 200 Lt, 20 Lt, 5 Lt, 1 Lt

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au). Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)"

**Effective:** October 2014

**Expires:** October 2016

GH410192/2



AUSTRALIAN FAMILY OWNED SINCE 1989

