



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

HI-TEC ROCK DRILL OILS

PRODUCT DESCRIPTION

Hi-Tec Rock Drill Oils provide effective lubrication and long trouble free service life to air operated equipment such as pneumatic drills, jumbo drills, jackleg drills, jackhammers, small air tools and motors, and airline oilers. **Hi-Tec Rock Drill Oils** are manufactured from oxidation resistant paraffinic base oils and proven rust and oxidation inhibitors, foam inhibitors and extreme pressure additives. **Hi-Tec Rock Drill Oils** contain a special balance of demulsibility control and tackiness essential for air operated lubrication.

PRODUCT BENEFITS

CORRECT VISCOSITY: a wide range of available viscosities of **Hi-Tec Rock Drill Oils** allows the selection of the optimum lubricant. The correct viscosity ensures that the misted lubricant feed from line oilers and other types of metering devices provides effective trouble free lubrication to every lubricated surface of air operated equipment. Incorrect viscosity leads to inadequate oil misting with resultant high wear rates, decreased equipment service life or even costly premature equipment failures.

EXTREME PRESSURE and ANTI-WEAR ADDITIVES in **Hi-Tec Rock Drill Oils** carry the high loads at the tool head which extend the working life of rock drills and other air tools. Metal to metal contact is avoided on heavily loaded components during the rotation and sliding motions even when adverse conditions of high temperature and high moisture are encountered.

RUST and OXIDATION INHIBITORS used in **Hi-Tec Rock Drill Oils** minimise deposit formation. The fine clearances of oil misting orifices, valves and passages in air tools are maintained to prevent partial blockages (caused by deposits) which reduce drilling speeds and cause premature equipment failure. All surface areas are effectively protected against rust formation in the normally moisture laden environments of air operated equipment.

NEGLIBLE ODOUR & TOXICITY in **Hi-Tec Rock Drill Oils**. This is a very important requirement when exhausting oil mist in confined areas and more particularly in underground mining where it is mandatory that the oil misting residues are not hazardous to the environment.

EXTRA ADHESIVENESS of **Hi-Tec Rock Drill Oils** further enhances lubrication in the presence of water. The tackiness maintains an oil film to sustain lubrication.

DIESELING INHIBITED. Under conditions of light load and when temperatures are high (withdrawal of percussion tools, etc.) auto-compression ignition may occur. This infrequent dieseling is minimised by the inclusion of a combustion suppressant.

ANTI-FOAMING CHARACTERISTICS **Hi-Tec Rock Drill Oils** avoid possible lubrication problems which can eventuate with lubricants which have not been adequately inhibited against foam.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

www.hi-tecoils.com.au

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

SPECIFICATIONS

<u>Property</u>	<u>ASTM Method</u>	<u>Typical Results</u>			
ISO Grade		150	220	320	460
Product Code		2814	2821	2817	2818
Density, Kg/Lt at 15°C	D.1298	0.895	0.899	0.902	0.905
Viscosity, cSt at 40°C	D.445	150	220	320	460
Pour Point, °C	D.97	-12	-9	-9	-9
Flash Point, COC, °C	D.92	250	270	280	285
Rust Prevention Characteristics	D.665	Pass	Pass	Pass	Pass
Copper Strip Corrosion	D.130	1a	1a	1a	1a

Available in: Bulk, 1000 litres, 200 litres and 20 litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: April 2016

Expires: April 2018

MR614060/1



AUSTRALIAN FAMILY OWNED SINCE 1989

