

MATERIAL SAFETY DATA SHEET

Product name: Truck 'n' Farm Grease

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)

ADDRESS: PO Box 322 Castle Hill NSW 1765
5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: Hi-Tec Truck 'n' Farm Grease

OTHER NAMES: None

MANUFACTURER'S PRODUCT CODE: HI7-1012-

USE: Lithium complex grease for automotive and industrial applications

ADDITIONAL INFORMATION: Refer to Product Information Sheet for additional information.

OTHER INFORMATION: Visit our website: www.hi-tecoils.com.au
Email: hitecoils@hi-tecoils.com.au

2. HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: NON-HAZARDOUS SUBSTANCE
NON-DANGEROUS GOODS
Hazard classification according to criteria of NOHSC.
Dangerous goods classification according to Australian Dangerous Goods Code.

RISK PHRASE (S):

IRRITANCY OF PRODUCT: Not classified as an irritant.

SENSITISATION OF PRODUCT: Not known to be a sensitiser.

TERATOGENICITY: No teratogenic effects known.

OTHER INFORMATION: Used greases may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used greases should be handled with caution and skin contact avoided as far as possible.

MATERIAL SAFETY DATA SHEET

3. IDENTIFICATION / COMPOSITION OF INGREDIENTS

CHEMICAL CHARACTERISTICS: Grease

INGREDIENTS:-

CHEMICAL ENTITY:	CAS No.	PROPORTION
Residual Oils and Distillates (Petroleum), Solvent Dewaxed	64742-62-	60% - 90%
Other ingredients determined not to be hazardous by quantity or nature		To 100%

4. FIRST AID MEASURES

HEALTH EFFECTS

SWALLOWED: This is not expected to be a means of entry during routine operation. Ingestion of small quantities should not cause irritation. If a large quantity is ingested seek immediate medical attention. Give water to drink. It may be necessary to induce vomiting. If vomiting occurs get immediate medical attention due to risk of aspiration into lungs.

EYE: May cause slight irritation to eyes. Immediately irrigate with copious amounts of water for at least 15 minutes. Eyelids to be held open. In all cases of eye contamination it is a sensible precaution to seek medical advice.

SKIN: May be mildly irritating to the skin. Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. High pressure injection through the skin requires **URGENT** medical attention for possible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns (Do not remove material).

INHALED: No data to indicate a toxic inhalation hazard. Inhalation of vapours or mist (generated at elevated temperatures) may cause irritation to the nose and throat. Remove victim from exposure to fresh air – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through face mask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage and seek urgent medical aid.

FIRST AID FACILITIES: Normal washroom facilities are generally suitable. Ensure an eye wash station and safety shower is available and ready for use.

ADVICE TO DOCTOR: Treat symptomatically.

OTHER INFORMATION: Keep water and mild soap near work site.

MATERIAL SAFETY DATA SHEET

5. FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

HAZARDS OF USE/STORAGE:	Product is a C2 combustible solid. This product is combustible if preheated.
HAZARDS FROM COMBUSTION PRODUCTS:	Combustion products may include: oxides of carbon, phosphorus, zinc, nitrogen and sulphur, a complex mixture of airborne unidentified organic and inorganic solid and liquid particulates.
FIRE-FIGHTING RECOMMENDATIONS:	If safe to do so, remove containers from path of fire. Keep storage tanks, pipelines, containers, fire exposed surfaces, etc. cool with water spray. Avoid spreading liquid and fire by water flooding.
PRECAUTION:	Water may cause splattering.
SUITABLE EXTINGUISHING MEDIA:	Use foam, carbon dioxide or dry chemical.
PROTECTIVE MEASURES:	Fire fighters should wear self-contained breathing apparatus if risk of exposure to products of combustion.
REACTIVITY:	May react with strong oxidising agents.

6. ACCIDENTAL RELEASE MEASURES

SPILLS & DISPOSAL:	Spills are easily contained due to the nature of the product. Caution: Slippery when spilt. Avoid accidents, clean up immediately.
	CLEAN-UP PROCEDURE - SMALL SPILLS (20L or less): Absorb or contain solid with sand, earth or spill control material. Shovel up using non-sparking tools and place in a sound labelled sealable container for subsequent safe disposal. Place leaking containers in a sound labelled drum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste.
	CLEAN-UP PROCEDURES - LARGE SPILLS (Greater than 20L): Transfer to a sound labelled, sealable container for product recovery or safe disposal. Treat residues as for small spills.
	PERSONAL PRECAUTIONS: Extinguish naked flames. Remove ignition sources. No smoking. Avoid sparks. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Evacuate the area of non-essential personnel. Shut off leaks, if possible without personal risk. Do not breathe vapours. Ventilate contaminated area thoroughly. Dispose of according to local regulations.
OTHER INFORMATION:	PROCEDURES IN CASES OF LEAKAGE OR BREAKAGE: Stop the source of the leak or release and contain spill if possible. Ventilate area. Use respirator and protective clothing outlined in this MSDS. Cover spill with inert absorbent earth. Use a stiff brush to mix thoroughly. Sweep up and place in a sound labelled disposable container. Scrub contaminated area with detergent and water using a stiff brush. Pick up liquid with additional absorbent material and place in a sound labelled disposable container. Prevent contamination of groundwater or surface water.

MATERIAL SAFETY DATA SHEET

7. HANDLING AND STORAGE

- PRECAUTIONS FOR SAFE HANDLING:** When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Ensure the appropriate personal protective equipment is used when handling this product. Ensure high level of personal hygiene is maintained when using this product. That is; always wash hands before eating, drinking smoking or using the toilet.
- SAFE STORAGE CONDITIONS:** Keep containers closed at all times. Store in a cool place out of direct sunlight. Store away from oxidising agents. Check containers regularly for leaks.
- CORROSIVENESS:** Not corrosive.
- STORAGE REGULATIONS:** Store in a well ventilated place away from ignition sources, oxidising agents, foodstuffs and clothing.
Keep containers closed when not in use.
Refer to AS 1940 – The Storage and Handling of Flammable Liquids, and
NOHSC: 1015 – National Standard for Storage and Handling of Workplace Dangerous Goods for further information.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- NATIONAL EXPOSURE STANDARDS:** No exposure standard has been established for this product. If the material is subjected to high temperature operations and mists or vapours are generated the Manufacturer recommends:
Time Weighted Average (TWA): 5 mg/m³ (oil mist).
Short Term Exposure Limit (STEL): 10 mg/m³ (oil mist).
- OTHER EXPOSURE INFORMATION:** Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).
- ENGINEERING CONTROLS:** Maintain concentration below recommended exposure limit. Special ventilation is not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standard or the Manufacturer's recommended exposure standard.
- RESPIRATORY PROTECTION:** A respirator is not normally required. Airborne concentrations should be kept at lowest level possible. If vapours, mists or dusts are generated and the recommended exposure limit for the product is exceeded, use appropriate AS/NZS 1715/1716 approved half –face filter respirator suitable for organic vapours or air supplied respirator are worn. Air supplied respirators should always be worn when the airborne concentration of the contaminant or the oxygen content of the air is unknown
- EYE PROTECTION:** Safety glasses, goggles or face shield as appropriate. If the material is used at elevated temperatures or under pressure a full face shield should be worn.

MATERIAL SAFETY DATA SHEET

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT)

HAND PROTECTION:	PVC, neoprene or nitrile gloves.
FOOTWEAR:	Enclosed footwear.
BODY PROTECTION:	Overalls or similar protective apparel.
HYGIENE MEASURES:	Always wash hands before eating, drinking, smoking or using the toilet. If contamination occurs, change clothing. Launder contaminated clothing before reuse. Discard internally contaminated gloves.
SPECIAL PROTECTIVE MEASURES:	Not flammable under normal conditions of use. Isolate from sources of heat, naked flames or sparks. Product is a combustible solid that will burn if preheated.

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM:	Grease
APPEARANCE:	Smooth tacky red grease.
COLOUR:	Red
ODOUR:	Mild
BOILING POINT:	Greater than 316°C
DENSITY @ 15°C (kg/L):	0.89 typical
FLASHPOINT (ASTM D-93), Closed Cup:	>200°C
FLAMMABILITY:	Combustible Solid.
SOLUBILITY IN WATER:	Not soluble.
VAPOUR PRESSURE:	N/A
DROP POINT:	Greater than 260°C
VISCOSITY @ 40 °C (mm ² /s):	Approximately 1100
AUTO-IGNITION TEMPERATURE:	Greater than 250°C
EXPLOSION PROPERTIES:	Not considered an explosion risk under normal conditions of use.
OTHER INFORMATION:	These physical data and other properties do not constitute a specification.

MATERIAL SAFETY DATA SHEET

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under normal conditions of use.
CONDITIONS TO AVOID:	Heat, direct sunlight, open flames or other sources of ignition.
INCOMPATIBLE MATERIALS:	Strong oxidising agents.
HAZARDOUS REACTIONS:	Will react with strong oxidising agents.
HAZARDOUS POLYMERISATION:	Will not occur.

11. TOXICOLOGICAL INFORMATION

TOXICOLOGY INFORMATION:	This product contains petroleum base oils, which may be refined by various processes including severe solvent extraction, hydro cracking and hydro treating. These oils have not been listed in the U.S. National Toxicology Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic or probably carcinogenic to humans. Oral LD50 ({{UDO1}}) :{{ UDO2}} mg/kg.
INHALATION:	Inhalation of mists or aerosols can produce respiratory irritation.
INGESTION:	Rats: Based upon testing of similar products and/or components, this material is considered to be relatively non-toxic with a LD50: > 2000 mg/Kg. May cause mild irritation of the mouth, throat and stomach with nausea and mild diarrhoea. Large amounts can cause vomiting which can lead to aspiration of vomited material into the lungs.
SKIN:	Rabbits: Based upon testing of similar products and/or components, this material is considered to be relatively non-toxic with a LD50: > 2000 mg/Kg. Based upon testing of similar products and/or components, this material is considered to be relatively non-irritating with a Primary Irritation Index: Greater than 0.5, but less than 3. Will have a de-fatting effect on the skin. Contact with skin may result in irritation.
EYE:	Rabbits: Based upon testing of similar products and/or components, this material is considered to be relatively non-irritating with a Draize Score: Greater than 6, but less than 15. May cause watering of eyes.
REPRODUCTIVE TOXICITY:	Rats: Based upon testing of similar products and/or components, this material is considered to show no adverse effects in either the mothers or their offspring by dermal exposure of pregnant rats. The relevance of these effects to humans is uncertain.
CHRONIC EFFECTS:	Sub chronic toxicity Rats: Based upon testing of similar products and/or components, this material is considered to show no adverse effects by dermal application to rats. Sensitisation Guinea Pigs: Based upon testing of similar products and/or components, this material is considered to show no evidence of skin sensitisation to guinea pigs during studies. Prolonged or repeated exposure may result in irritation, with the possibility of dermatitis.

MATERIAL SAFETY DATA SHEET

11. TOXICOLOGICAL INFORMATION (CONT)

MUTAGENICITY: Mutagenic effects not known.

CARCINOGENICITY: Mice: Based upon testing of similar products and/or components, this material is considered to show no evidence of carcinogenic effects by chronic mouse skin painting studies.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Leaching and penetration through soils is generally regarded as resulting in long-term persistence. Fresh or used product may be harmful to aquatic life. Do not allow material to enter drains or watercourses.

13. DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATIONS: Dispose of according to federal, E.P.A. and state regulations.

14. TRANSPORT INFORMATION

TRANSPORT INFORMATION: Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

15. REGULATORY INFORMATION

POISON SCHEDULE: Not scheduled.

PACKING & LABELLING: No special packaging or labelling requirements.

AUSTRALIAN INVENTORY STATUS: All components are listed or exempted.

16. OTHER INFORMATION

CONTACT PERSON/POINT: General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Material Safety Data Sheets are updated frequently. Please ensure you have a current copy.

MATERIAL SAFETY DATA SHEET

16. OTHER INFORMATION (CONT)

- LITERATURE REFERENCES:
- * NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
 - * NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
 - * NOHSC: 10005 List of Designated Hazardous Substances.
 - * NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
 - * NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
 - * NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
 - * NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
 - * NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
 - * NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.
 - * SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
 - * ADG: Australian Dangerous Goods Code
 - * MSDS of component materials.

LAST CHANGE: Supersedes document issued: 10th June 2009
Reason/s for revision: Minor editorial changes.

GH110160/1

END OF MSDS