

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

## DUCT DATA SHEET

## **HI-TEC X55 SOLVENT**

## PRODUCT DESCRIPTION

Hi-Tec X55 Solvent is a wide boiling range, rapidly evaporating, residue free solvent used for processing, cleaning and degreasing in many industries including printing, paints, adhesives and rubber manufacture.

-30°C Hi-Tec X55 Solvent does not mix with water, is highly flammable with a flash point of and can form explosive mixtures with air.

Hi-Tec X55 Solvent does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

<u>METHOD</u>	RESULTS
ASTM D4052	0.682
ASTM D156	25
IP 170	-30
ASTM D86	67
ASTM D86	135
GC	80
GC	17
GC	3
GR 333	0.05
ASTM D611	62
ASTM D2624	400
	ASTM D4052 ASTM D156 IP 170 ASTM D86 ASTM D86 GC GC GC GC GR 333 ASTM D611

Item Code: HI8-3570-

Available In: 200 Litres, 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: October 2014 Expires: October 2016

GH411092/1





