



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

HD HAMMER CHISEL PASTE

DESCRIPTION

Hi-Tec HD HAMMER CHISEL PASTE is a grease formulated to provide lubrication of hydraulic hammers and is fortified with solids to prevent galling and seizing. It has an operating temperature range of -30 to $+200^{\circ}\text{C}$ with protection up to 1000°C provided by the solids content.

TYPICAL TESTS

	<u>ASTM</u>	<u>VALUE</u>
NLGI		2
Appearance		Copper / Gray
Gelling Agent		Calcium Sulphonate Complex
Penetration, Worked @ 25°C	D.217	250 – 290
After 10,000, % change		+/- 5
Dropping Point, min $^{\circ}\text{C}$	D.2265	260
Solids, graphite and copper %		14
4-Ball Weld, kg	D.2596	800
4-Ball Wear, Scar Diameter, mm	D.2266	0.60
Rust Prevention Characteristics	D.1743	Pass
Mineral Oil, Viscosity, cSt @ 40°C	D.445	200 - 240
@ 100°C	D.445	18 - 20

Product Code: HI7-1035-

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: August 2015

Expires: August 2017

MR511080/1



AUSTRALIAN FAMILY OWNED SINCE 1989

