



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

KEROSENE

PRODUCT DESCRIPTION

Hi-Tec Kerosene is a premium quality kerosene for use in various applications including heating, cooking and refrigeration. It can be used as a lighting fuel, to power engines and also as a solvent for degreasing and other industrial applications.

HAZARDOUS IDENTIFICATION

Hi-Tec Kerosene is a combustible hydrocarbon liquid, **Class: 3 Dangerous Good Flammable Liquid UN 3295** with a flash point of 38°C. Avoid contact with skin, eyes and inhaling the vapours of this product. Please refer to the MSDS for further safety information.

TYPICAL PROPERTIES

UNITS

RESULTS

Appearance		Colourless liquid
Flash Point	°C	38
Boiling Point range	°C	145 – 300
Auto Ignition Temperature	°C	230

Product Code: HI8-3220

Available In: 200Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: October 2015

Expires: October 2017

MR514080/1



AUSTRALIAN FAMILY OWNED SINCE 1989

