



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

## PRODUCT DATA SHEET

### ROADRANGER SAE 50

#### DESCRIPTION

**Roadranger SAE 50** is mineral based blended oil for use in Road ranger gearboxes and for automotive and industrial applications where extreme pressure properties are not required. The high viscosity index and low pour point provide a tough, highly adhesive film to protect gear teeth and bearings against wear.

**Roadranger SAE 50** can be used where manufacturer's recommendation is for API service GL-1 or GL-2 gear oil. **Roadranger SAE 50** can be used to lubricate various manual transmissions in mild gear oil applications in some spiral bevel axle assemblies and worm gear drives on commercial, farm and truck equipment.

#### CHARACTERISTICS

API GL-1, GL-2

Gear Oil Viscosity Classification: SAE 90

#### TYPICAL TEST

#### Roadranger SAE 50

Product code:	2519
Viscosity, cSt at 100°C	17.6
Viscosity Index	100
Flash Point, COC °C	210
Pour Point, °C	- 6

#### AVAILABLE IN:

200 Lt, 60 Lt, 20 Lt

"The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes"

Item Code: 2519

Effective: August 2015

Expires: August 2017

MR518072/1



AUSTRALIAN FAMILY OWNED SINCE 1989

