

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

ROADRANGER SAE 50

DESCRIPTION

Roadranger SAE 50 is mineral based blended oil for use in Road ranger gearboxes and for automotive and industrial applications where extreme pressure properties are not required. The high viscosity index and low pour point provide a tough, highly adhesive film to protect gear teeth and bearings against wear.

Roadranger SAE 50 can be used where manufacturer's recommendation is for API service GL-1 or GL-2 gear oil. **Roadranger SAE 50** can be used to lubricate various manual transmissions in mild gear oil applications in some spiral bevel axle assemblies and worm gear drives on commercial, farm and truck equipment.

CHARACTERISTICS

API GL-1, GL-2

Gear Oil Viscosity Classification: SAE 90

TYPICAL TEST	Roadranger SAE 50
Product code:	2519
Viscosity, cSt at 100°C	17.6
Viscosity Index	100
Flash Point, COC °C	210
Pour Point, °C	- 6

AVAILABLE IN: 200 Lt, 60 Lt, 20 Lt

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner. Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: 2519

Effective: August 2015 Expires: August 2017

MR518072/1





