



PRODUCT DATA SHEET

FAST 2 SEMI SYN TWO STROKE OIL

PRODUCT DESCRIPTION

Hi-Tec Fast 2 Semi Syn Two Stroke Oil is designed to be used in high performance top tier two stroke motor cycle engines, chain saws and power tools. It is formulated from a high quality mineral base stock with detergent additives to create a modern low ash low smoke lubricant.

Hi-Tec Fast 2 Semi Syn Two Stroke Oil has consistently given excellent engine cleanliness and freedom from ring sticking results under controlled test conditions. Its performance is based upon practical field experience involving the continual development and improvement of the lubricant additive system in high performance motorcycle racing engines.

Hi-Tec Fast 2 Semi Syn Two Stroke Oil is manufactured with self-mixing solvents and should be used at the fuel/oil ratio recommended by the engine manufacturer.

Hi-Tec Fast 2 Semi Syn Two Stroke Oil may be used in small to medium sized water-cooled engines, which may not be sensitive to low ash levels. However it should not be used in water-cooled outboard engines.

Hi-Tec Fast 2 Semi Syn Two Stroke Oil meets the requirements of the API TC, JASO FA, FB, FC and FD, and ISO-L-EGB, -EGC and -EGD and TISI specifications.

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property	ASTM Method	Results
Density, kg/Lt @ 15.0°C	ASTM D.1298	0.851
Viscosity cSt @ 40°C	ASTM D.445	42
Nitrogen Content, %wt	ASTM D.5291	0.02
TBN, mg KOH/g	ASTM D.2896	1.15
Ash, % wt	Calculated	0.10

Available in:

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI8-2126A

Effective: March 2017

Expires: March 2019

GH713001/2

