



MULTITRANS ATF

Hi-Tec Multitrans ATF is a premium full synthetic automatic transmission fluid with exceptional oxidative resistance, antiwear performance and frictional stability. It provides excellent antirust properties, and sludge & varnish control. It is designed for use in North American, European and Asian vehicles.

SPECIFICATIONS

Product Code	HI3-2684
JASO	JASO 1-A
Performance	Ford Mercon® V, Allison C-4, TES-295, JASO 1-A; GM Dexron® IIIH; Ford Mercon and Ford / BTR 4 speed 85LE and 95LE fluids; AE, Aisin Warner, Audi, BMW, Chrysler, Daimler, Ford Mercon®, GM Dexron® III (H), Honda, Hyundai, Jaguar, JASO, JATCO, JWS, Kia, Mazda, Mercedes Benz, Mitsubishi, Nissan, Rover, Saab, Subaru, Toyota, Volvo, VW and ZF; commercial applications
Product Sizes	1L, 5L, 20L, 60L, 200L, 1000L and Bulk



MULTITRANS PLUS ATF (SYN ATF)

Hi-Tec Multitrans Plus ATF is a premium full synthetic automatic transmission fluid designed and OEM approved to meet the long drain ZF TE-ML 14C and 20C performance standards, as well as being suitable for use in many North American, European and Asian vehicles.

SPECIFICATIONS

Product Code	HI3-2677
JASO	JASO 1-A
ZF	ZF TE-ML 14C suitable for use in ZF Ecomat powershift transmissions in buses and trucks, ZF-TE ML 20C for ZF Ecolife Transmissions in buses and trucks
OEM Approvals	ZF TE-ML 04D, 14C, 16M, 20C; Voith 55.6336.XX (G1363)
Performance	Ford Mercon® V; Allison C-4; MAN M339 F, V-1, Z-1, Voith 55.6335.XX (G607), Volvo 97340 and 97341; GM Dexron® IIIH; Ford Mercon® fluids. All other specifications fulfilled by Hi-Tec Multitrans ATF
Product Sizes	20L, 60L and 200L



ATF DX6

Hi-Tec ATF DX6 is a premium full synthetic automatic transmission fluid specially formulated to meet the requirements of the General Motors Dexron® VI specification.

SPECIFICATIONS

Product Code	HI3-2681
Performance	GM Dexron® VI; Ford Mercon® LV; Ford Mercon® SP; Toyota WS
Suitable for	ATF DX VI is also suitable for many hydraulic systems where ISO 22 or 32 hydraulic fluids or SAE 10W engine oils are recommended.
NOTE	Do not use for CVT, DCT or Ford M2C-33F & M2C-33G (Type F & G transmissions)
Product Sizes	5L, 20L, 60L, 200L, 1000L and Bulk



UNIVERSAL CVT

Hi-Tec Universal CVT Transmission Fluid is a premium full synthetic Continuously Variable Transmission (CVT) fluid, with excellent anti-foaming, anti-shudder, anti-scuffing and shear stability properties. It has been successfully demonstrated in varying types of CVTs with road tests in numerous vehicles. It is suitable for use in many CVT transmissions especially Audi/ VW, Honda, Mini Cooper and Subaru.

SPECIFICATIONS

Product Code	HI3-2676
Performance	Audi/ VW/ VW Chain (TL 52180 G 052 180; G 052 516); BMW (8322 0 136 376, 8322 0 429 154, EZL 799A); Daihatsu (CVTF-DC, CVTF DFE); Dodge/Jeep/MOPAR (NS-2, CVTF+4); Ford Chain and Belt (CVT23, CVT30, Mercon C); GM/Saturn (DEX-CVT); Honda (HMMF, HCF-2, CVT-F 05); Hyundai / Kia (SP-CVT 1); Mazda (CVTF, CVT3320); Mercedes Benz (236.20); Mini Cooper (EZL 799A); Mitsubishi Diaqueen (CVTF-J1, CVTF-J4*); Nissan (NS-1, NS-2, NS-3*); Punch (EZL 799A); Shell Green 1V; Subaru (NS-2, Lineartronic CVTF, K0425Y0710, CV-30, High Torque CVT Fluid); Suzuki (TC, NS-2, CVTF Green 1, CVTF Green 2*); Toyota/Lexus (TC, FE*) *Low viscosity CVT fluid
Product Sizes	1L, 5L, 20L, 60L and 200L



FAST 2 SYN ATF

Hi-Tec Fast 2 Syn ATF is a fully synthetic, super premium multifunctional fluid for motorcycles requiring Dexron® III lubricants. It is also suitable for use in automatic and powershift transmissions and industrial and mobile hydraulic systems. Hi-Tec Fast 2 Syn ATF achieves cleaner transmissions and more reliable operation due to the excellent thermal and oxidative stability, it provides excellent high and low temperature properties and performance due to the use of high viscosity index synthetic base oils.

SPECIFICATIONS

Product Code	HI3-2680A
Performance	Dexron® III (H)
Product Sizes	1L and 5L



DCT FLUID

Hi-Tec DCT Fluid is an advanced lubricant for dual clutch transmissions (DSG Direct Shift Gearbox). This synthetic oil provides smooth shifting, anti-shudder performance resulting in fuel economy benefits and superior transmission response due to its optimized frictional characteristics and wear protection. It can be used in DCT transmissions of passenger cars and vans which use Getrag and ZF equipment including Audi, BMW, Citroen, Ferrari, Fiat, Ford, Mercedes-Benz, Mitsubishi, Nissan, Peugeot, Porsche, Renault, Seat, Skoda, Volkswagen and Volvo vehicles.

SPECIFICATIONS

Product Code	HI3-2674
Performance	Audi/Seat/Skoda/Volkswagen VW TL 052 182, VW TL 052 529; BMW (Getrag) 83 22 2 148 578, 83 22 2 148 579, 83 22 0 440 214, 83 22 2 147 477, DCTF-1; Ferrari TF DCT-F3; Fiat BOT 341; Ford/Getrag WSS-M2C936-A (BOT 341); Mercedes Benz MB 236.21 (001 989 03), MB 236.25; Mitsubishi MZ320065 (Dia Queen SSTF-I); Peugeot/Citroen 9734.S2; Porsche 999.917080.00 (FFL-3); Renault BOT450; Shell DCT M-1 and Volvo 1161838, 1161839.
Product Sizes	5L, 20L, 60L, 200L and Bulk

PREMIUM MINERAL ATF FLUIDS



ATF TYPE 95 LE

Hi-Tec Type 95 ATF is the premium Automatic Transmission Fluid for the Ford 4 speed automatic transmissions made by BTR for the 95LE in V8 and the 85LE in 6-cylinder models.

SPECIFICATIONS

Product Code	HI3-2685
Performance	Type A Suffix A (TASA); Caterpillar TO-2; Ford Mercon®; GM Dexron® II; Volvo 97325
Product Sizes	5L, 20L, 60L, 200L, 1000L and Bulk



ATF DX3

Hi-Tec ATF DX3 is an automatic transmission fluid for use in older automatic transmissions requiring GM Dexron® III or Ford Mercon® performance. It is also suitable for use in other transmissions, where the Allison C4 and TES-389 performance levels are called for as well as various power steering, pump and hydraulic applications.

SPECIFICATIONS

Product Code	HI3-2688B
ZF	ZF TE-ML 05L, 09L, 14A & 21L
Performance	General Motors Dexron® III; Ford Mercon®, XL-12; Allison C-4, TES-389B; Caterpillar TO-2; Power Steering Fluid applications; BTR 95LE, BTR 85LE; Voith H55.6335.xx; Volvo 97325, 97335 & 97340; Auto Trak II; Many hydraulic systems and smaller rotary air compressors.
NOTE	Do not use for CVT, DCT or Ford M2C-33F & M2C-33G (Type F & G transmissions)
Product Sizes	1L, 5L, 20L, 60L, 200L, 1000L and Bulk



TRANS SAE 10W, 30, 50, 60

Hi-Tec TRANS SAE oils are specialised Transmission and Drive Train Oil (TDTO) which have been specifically formulated to meet the requirements of the Caterpillar TO-4 and the Allison C-4 specifications.

Hi-Tec TRANS SAE oils greatly reduce gear wear, improve friction control, promote long life in transmissions and brakes, and ensure less brake noise and increased rimpull.

SPECIFICATIONS

Product Code	HI3-2510 (10W); HI3-2515 (30); HI3-2519 (50); HI3-2520 (60)
API	GL-4 Wear Protection; GL-3 and CF & CF-2 (SAE 30, 40, and 50 in case of misapplication as engine oils)
ZF	ZF TE-ML 03C; (SAE 10W and SAE 30); ZF-TE ML 07F
Performance	CAT TO-4 (Version 2005); Komatsu KES 07868.1 powertrain fluid, Komatsu Dresser; Dana Powershift: (SAE 10W and SAE 30); Allison C-4 and Allison C-3; Vickers 35 VQ25; SAE 10; Eaton:SAE 50; Spicer Clark-Hurth: (SAE 10W and SAE 30); Tremec/TTC: SAE 50
Product Sizes	20L, 200L, 1000L and Bulk



POWER STEERING FLUID

Hi-Tec Power Steering Fluid is a new generation premium power steering fluid, suitable for most passenger cars and light commercial steering systems.

SPECIFICATIONS

Product Code	HI3-2688C
Benefits	<ul style="list-style-type: none"> Effective anti-wear properties help minimise wear and maximise system life. Effective foam control and oxidation provides smooth operation and longevity of fluid.
Product Sizes	500ml