



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

PREMIER LITE SP/CF 10W/30

PRODUCT DESCRIPTION

Premier Lite SP/CF 10W/30 is the ultimate in protection and performance designed for the professional workshop. This superior quality engine oil is made using premium mineral base oils. It meets the API SP performance level which has been specifically developed to address Low-Speed Pre-Ignition (LSPI) and timing chain wear in small turbocharged petrol engines. It is suitable for most types of petrol and four stroke diesel engines, including those engines with small clearances and those operating under the most severe and varied operating conditions, such as high temperature motorway driving or low temperature stop-and-go driving.

Premier Lite SP/CF 10W/30 is also ideal for cold starting situations because of its excellent low temperature fluidity characteristics whilst also providing protection at operating temperatures. It provides increased engine life since the wear rates associated with older quality engine oils is decreased by the higher performance levels.

SPECIFICATIONS

Premier Lite SP/CF 10W/30 meets or exceeds the following demanding performance levels:

API: SP, SN, SM, CF

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property	ASTM Method	Results
Density (kg/Lt) @ 15°C	D-1298	0.867
Viscosity (cSt) @ 100°C	D-445	11.1
@ 40°C	D-445	81.2
Viscosity Index	D-2270	124
Flash Point COC (°C)	D-92	216
Pour Point (°C)	D-97	-27

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 10 Litres, 6 Litres, 5 Litres and 1 Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI1-2119

Effective: March 2024

MR423012/1



AUSTRALIAN FAMILY OWNED SINCE 1989

