



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TRUCK AND FARM GREASE

PRODUCT DESCRIPTION

Truck and Farm Grease is a red, semi-synthetic, smooth, tacky grease recommended for use in bearings, chassis parts, gears and couplings in automotive, agricultural, marine and industrial applications.

Truck and Farm Grease is used for bearing lubrication from normal to unusually severe load conditions, for high and low temperature applications, and situations where water spray or ingress is encountered.

CHARACTERISTICS

Truck and Farm Grease is manufactured with lithium complex thickener combined with high quality paraffinic and polybutene base stocks, extreme pressure (EP) additives, rust, oxidation and corrosion inhibitors, tackiness additives and effective extreme pressure additives to cater for unusually high load service conditions.

Truck and Farm Grease protects against wear on all moving parts from shock loadings to unusually high-load service. It helps prevent scuffing and further assists in wear prevention because it has excellent shear stability allowing it to withstand high load extreme pressure situations.

Truck and Farm Grease resists "squeeze-out" from lubricated surfaces under heavy load conditions. It has been specially formulated to include a shear-stable tackiness agent which, unlike other lithium complex greases, has the extra tenacity for "stay-put" lubrication, and the ability to resist water washout or water spray dilution.

Truck and Farm Grease has high shear stability which ensures long service life particularly in sealed anti-friction bearings. The excellent resistance to mechanical shear combined with high film strength maintains grease consistency for extended lubrication service.

Truck and Farm Grease is oxidation inhibited for long service life, and rust and corrosion inhibited to provide effective lubrication under difficult corrosive environments or in rust prone service situations. The inhibitors protect most metal components under these adverse conditions.

SPECIFICATIONS

Specifications: ISO 6743-9: L-XBEB2 and DIN 51502: KP2P -20.

RECOMMENDATIONS

INDUSTRIAL and GENERAL - Recommended for ball, roller, needle and slow speed plain bearings operating under all service conditions. **Truck and Farm Grease** has an excellent service record under unusually high load and/or shock load service conditions.

AUTOMOTIVE - Recommended for chassis universal joints, and other general lubrication areas in cars, trucks, tractors, trailers etc.

Care should be taken if using **Truck and Farm Grease** in wheel bearings as it may be too heavy for this application. Preferably use **Lithplex Tac EP2** grease for wheel bearings.

Hi-Tec suggests that the equipment manufacturers' recommendations for grade, performance requirements and general operating conditions should be checked prior to use.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL PROPERTIES

Description	Method	Results
Colour/Appearance	Visual	Red/Tacky
NLGI	-	2
Thickener	-	Lithium Complex
Viscosity (cSt) @ 40°C	ASTM D445	1600
Worked Penetration (60 strokes)	ASTM D217	265-295
Dropping Point (°C)	ASTM D2265	250
4-Ball Weld Load (kg/F)	ASTM D2596	315
Operating Range (°C)	-	-20 to 160

Available in: Bulk, 180kg, 20kg and 450g cartridges

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI7-1012

Effective: September 2026

MR629032/1



AUSTRALIAN FAMILY OWNED SINCE 1989

