



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

### AFAB G93 PREMIX COOLANT

#### PRODUCT DESCRIPTION

**Hi-Tec AFAB G93 Premix Coolant** is a premixed inhibitor solution for use in the cooling system water of internal combustion engines that do not require anti-freeze protection.

#### BENEFITS

- High performance corrosion inhibitor.
- Excellent protection against cavitation.
- Compatible with zinc coated equipment as it is nitrite free.
- Prolongs the working life of water pumps and heat exchangers.

#### APPLICATION

**Hi-Tec AFAB G93 Premix Coolant** is designed to be used as received. It provides excellent protection against cavitation and corrosion to all metals and alloys used in engine cooling systems, such as aluminium, ferrous and yellow metals. It is especially appropriate for use in heavy-duty engines used in trucks, ships and locomotives.

#### DIRECTIONS FOR USE

When the vehicle engine is cool, drain the cooling system (including the heater) as per the vehicle owner's manual. Thoroughly flush and rinse the cooling system. Fill the cooling system with the correct volume of **Hi-Tec AFAB G93 Premix Coolant** (as per the vehicle owner's handbook) after reconnecting all hoses, drain plugs, etc.

Check the level of the **Hi-Tec AFAB G93 Premix Coolant** and top up after running the engine to operating temperature and allowing it to cool again.

Always consult the equipment manual for the manufacturer's recommendations.

#### PROPERTIES

Appearance:	Green liquid
Density (g/cm <sup>3</sup> ):	1.05 – 1.07 Typical
pH:	9.3 – 9.5
Boiling Point, °C:	>100
Flash Point, °C:	>120
Ignition Temperature, °C:	>240
Freezing Point, °C:	< 0



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

Available in: **XXX**

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au). Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)".

Item code: HI8-**XXXX**

Effective: May 2017

Expires: May 2019

MR715090/5



AUSTRALIAN FAMILY OWNED SINCE 1989

