



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

ATF DX6

PRODUCT DESCRIPTION

ATF DX6 is a synthetic-based automatic transmission fluid specially formulated to meet the requirements of the General Motors Dexron® VI specification.

ATF DX6 is recommended for transmissions used in most General Motors, Holden, Isuzu, and Opel cars and Hydramatic® transmissions used in a range of other vehicles. It is fully backwards compatible and can be used whenever Dexron® III and/or Dexron® II are recommended in GM vehicles and transmissions. It supersedes earlier Dexron® specifications: Dexron® III H, G and F; Dexron® II E and D and Dexron® fluids in GM automatic transmissions. These include Hydramatic® and automatic transmissions in Holden, Chevrolet, Pontiac, Buick, etc.

ATF DX6 may be used for long drain service in many European commercial vehicle applications. It may also be used in power steering units for many cars, light commercial vehicles and tractors except where specialist fluids are recommended e.g., Honda, Mercedes-Benz, SAAB.

BENEFITS

- Enhances the performance of new and older GM transmissions.
- Provides consistent shift performance to allow for longer service intervals.
- Extends transmission fluid life and resists fluid breakdown at higher operating temperatures.
- Provides excellent oxidative stability under severe conditions.
- Provides friction stability and durability combined with excellent wear protection
- Excellent durability for taxis, vehicles used for towing and other hard working applications.
- Reduces sludge and varnish build up.
- Protects transmission gears and allows them to operate smoothly.
- Maintains lubricity.
- Flows well for cold start-up.

SPECIFICATIONS

ATF DX6 meets or exceeds the following demanding performance requirements:

Acura DW-1

Audi G 055 005; G 055 540; G 055 162; G 060 162

BMW P/N 81 22 9 407 858/859; 83 22 0 142 516; 83 22 0 397 114; 82 22 2152426

Chrysler MB236.12; P/N 05127382AA; 68043742AA; 68157995AA

Daimler MB236.12; .14; .15 .41

Dodge MB236.12; P/N 05127382AA; 68043742AA; 68157995AA

Ford PN XT-10-QLV; XT-6-QSP/DSP; MERCON LV; SP

GM AW1; V1; P/N 88863400; 888663401

GMC AW1; V1; P/N 88863400; 888663401

Honda DW-1

Hyundai NWS-9638 T-5; SP-IV; SPH-IV

Infinity Matic S

Jaguar 02JDE 26444

Jeep MB236.12; P/N 05127382AA; 68043742AA; 68157995AA

Kia NWS-9638 T-5; SP-IV; SPH-IV

Land Rover P/N TYK500050; P/N LR023288

Lexus WS

Lincoln P/N XT-10-QLV; XT-6-QSP/DSP; MERCON LV; SP

Maserati P/N 231603

Mazda FZ



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Mercedes MB 236.12, .14, .15, .41
Mercury P/N XT-10-QLV; XT-6-QSP/DSP; MERCON LV; SP
Mini P/N 81 22 9 407 858/859; 83 22 0 142 516; 83 22 0 397 114; 82 22 2152426
Mitsubishi J3; PA Fluid
Nissan Matic S
Opel AW1; V1; P/N 88863400; 888663401
Porsche P/N 000 043 304 00
Saab P/N 93 165 147 - AW-1
Saturn AW1; V1; P/N 88863400; 888663401
Scion WS
Shell, 3353; 134; M-1375.4
Toyota WS
Volkswagen G 055 005; G 055 540; G 055 162; G 060 162
ZF Lifeguard Fluid 6; 6 Plus; 8; 9.

ATF DX6 is also suitable for many hydraulic systems where ISO 22 or 32 hydraulic fluids or SAE 10W engine oils are recommended.

Note: **DO NOT** use for CVT, DCT or Ford M2C-33F and M2C-33G (Type F and G) transmissions

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

TYPICAL PROPERTIES

Property	Results
Colour	Red
SAE Viscosity Grade	0W-20
Specific Gravity @ 15°C (g/ml)	0.850
Viscosity @ 100°C (cSt)	6.51
Viscosity @ 40°C (cSt)	35.32
Viscosity Index	140
Pour Point (°C)	-54
Flash Point PMCC (°C)	200

Available in: Bulk, 1000 Litres, 200 Litres, 60 Litres, 20 Litres, 5 Litres and 1 Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI3-2681

Effective: 28 November 2019

KH911182/1



AUSTRALIAN FAMILY OWNED SINCE 1989

