



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

DD 50 COOLANT GREEN (Heavy Duty Diesel Engine Coolant Premix)

PRODUCT DESCRIPTION

DD 50 Coolant Green is a heavy duty diesel engine coolant premix, luminescent yellow in colour, superior, fully formulated Hybrid technology engine coolant. This hybrid technology coolant has the advantage of being more robust than both conventional and organic acid technology (OAT) engine coolants. This low silicate, phosphate and amine free product is recommended for use in automotive (aluminium compatible), light duty and heavy-duty diesel applications namely on-road truck, off-road, farm and marine. It provides excellent high temperature aluminium protection.

DD 50 Coolant Green does not require an initial charge of supplemental coolant additives (SCAs) upon initial fill in heavy duty diesel applications as the product is specially formulated to protect heavy duty diesel wet sleeve liners. SCA addition is application dependant and should only be added as and when required by the vehicle's OEM. This coolant is compatible with coolant filters and heavy duty diesel SCAs and coolant extenders.

BENEFITS

Advantages of using **DD 50 Coolant Green**:

- Low silicate
- Phosphate and amine free
- OEM approved
- Hard water compatible
- No initial SCA requirement at initial fill
- Universal use, fully meets or exceeds standard industry requirements for automotive, light duty, and heavy duty diesel applications
- Product is compatible with both conventional and OAT coolants (although to get best performance [regarding issues such as extended life and time between SCA additions] it is best to flush the old coolant and replace with **DD 50 Coolant Green**)
- Product is compatible with standard SCAs and coolant extenders
- Extended life 6 years, 12,000 hours or 1,000,000 km whichever comes first

SPECIFICATIONS

DD 50 Coolant Green meets or exceeds the following demanding performance requirements:

- ASTM D-3306, D-4985, D-6210
- Caterpillar EC1
- Cummins 14603
- Detroit Diesel 7SE 298
- Daimler Chrysler MS 7170, MS 9769
- Ford ESE-M97B44A, ESE-M97B18-C
- Ford WSS-M97B51-A1
- Freightliner 48-2288D
- GM 1825M, 1899M, GM Heavy Truck
- Hyundai
- JIS K2234
- Kenworth RO26-170-97
- Landrover
- MACK Trucks
- Kubota Extended Life Premix Coolant
- MAN 324
- Mercedes Benz DBL 325
- MTU MTL 5048
- New Holland WSN-M97B18-D
- PACCAR
- Peterbilt 8502.002
- Perkins
- Saab-Scania 6901
- SAE J1034, J1941
- TMC RP 329
- Volvo Heavy Truck
- White Star
- US Federal A-A-870-A
- Deutz 0199-99-1115/6



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

DD 50 Coolant Green is approved by:

MTU

Detroit Diesel

Daimler Chrysler

DD 50 Coolant Green provides exceptional summer cooling and excellent freezing protection during winter. It provides excellent value as an aluminium compatible, universal, long life engine coolant.

Always consult your vehicle owner's manual for the manufacturer's recommendations.

PERFORMANCE TESTING

Coupon	ASTM D-1384 Glassware Corrosion		ASTM D-2570 Simulated Service	
	Test Results ¹	Max. Spec. ¹	Test Results ^{1,2}	Max. Spec. ¹
Copper	1.7	10	1.1	20
Solder ³	4.3	30	21.6	60
Brass	0.6	10	1.6	20
Steel	0.1	10	+0.8	20
Cast Iron	+0.8	10	+1.2	20
Aluminium	+0.3	30	+2.5	60

1. Wt. /loss coupon in mg. 2. Copper/brass radiator results. 3. Regular 70/30 lead on copper/brass coupons.

ASTM Test Procedure	Test Results	Specification
D4340 Heat Rejecting Aluminium Corrosion	0.16 mg/cm ² /week	1.0 maximum
D2809 Aluminium Water Pump Cavitation-Erosion Corrosion (rating from 1 to 10)	10	8 minimum

Shelf-life stability: minimum 2 years from date of manufacture



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL PROPERTIES

Property	ASTM Method	Typical Results
pH	D-1287	7.6 - 8.5
Reserve Alkalinity (mL)	D-1121	3 min.
Specific Gravity (15.6°C/60°F)	D-1122	1.065 - 1.075
Freeze Point	D-1177	-37°C/-34°F
Foam Volume (ml)	D-1881	50 max.
Break Time (sec)	D-1881	5 max.
Flash Point	D-92	116°C/240°F
Fire Point	-	120°C/248°F
Ash Content (% wt)	D-1119	2.5 max.
Odour	-	Characteristic
Colour	-	Luminescent Yellow
Total Glycols (% wt)	-	50.0 min.
Inhibitors and dye (% wt)	-	2.5 max.
Chloride ppm	D-3634	25 max.
Silicon (ppm)	ICP	93 max.

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 5 Litres and 1 Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI8-3090

Effective: February 2020

MR022072/1



AUSTRALIAN FAMILY OWNED SINCE 1989

