

**Hi-Tec Oil Traders Pty Ltd** ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

## PRODUCT DATA SHEET

## **DE-RUST OIL**

#### PRODUCT DESCRIPTION

**De-Rust Oil** is multi-functional water displacing fluid, possessing effective rust preventative, fingerprint suppressant, penetrating fluid and lubricant properties. **De-Rust Oil** performs many every day type services in the home as well as industry, having rural, transport, automotive and marine applications. It is non-toxic and will not stain.

## **APPLICATIONS**

## Water Displacer:

**De-Rust Oil** very rapidly displaces water on all wet surfaces. It is very effective in providing instant engine starts in wet automobiles, motorcycles, outboard engines and lawn mowers, etc.

#### Rust Preventative:

**De-Rust Oil** is a very effective rust preventative for short-term indoor applications. It forms a protective film to inhibit rust and corrosion to 101 items, such as metal components, tools, sporting equipment, locks, hinges, lawn mowers, outboard motors and many more.

#### Lubricant:

**De-Rust Oil** lubricating properties are employed for every day services; squeaky hinges, locks, latches, pulleys, car doors, sewing machines, outboard motors, lawn mowers and any more. The lubricant film is transparent and is non-staining.

## Penetrating Fluid:

**De-Rust Oil**, assists in loosening "frozen" nuts and fasteners. The freely flowing low viscosity of **De-Rust Oil** allows it to penetrate between tightly adhering surfaces and softens the bonding oxidation matrix so that nuts and other frozen components can be loosened and removed.

### **TYPICAL PROPERTIES**

Property Results

Appearance Clear, amber liquid Density @ 15°C, kg/L 0.9 approximately

Flash Point, °C 36 Boiling Point, °C >146

#### TRANSPORT AND HANDLING

UN No. 3295

Dangerous Goods Class 3, Flammable Liquids

Hazchem Code 3Y Packaging Group III

Refer to the Safety Data Sheet for safety instructions prior to handling.









**Hi-Tec Oil Traders Pty Ltd** ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

# **PRODUCT DATA SHEET**

**Available in:** 200 Litres, 20 Litres and 5 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at <a href="www.hi-tecoils.com.au">www.hi-tecoils.com.au</a>. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI8-3110

Effective: March 2020

MR023040/1



