



PRODUCT DATA SHEET

DRAWING OIL 1755S (Evaporative Stamping Fluid)

APPLICATION

Hi-Tec Drawing Oil 1755S is an evaporative stamping fluid designed for stamping of laminated sections. The product leaves a thin film of corrosion inhibitors that prevents sticking and protects the parts from corrosion. It is composed of a blend of inorganic sulphonates in a de-aromatised and refined hydrocarbon liquid.

BENEFITS

- Leaves minimal residue on the parts;
- Eliminate the cleaning stage;
- Good anti-wear performance and stable low friction;
- Low consumption, optimum performance from thin films;
- Low odour

USAGE

Use Concentration: as it is received.

COMPATIBILITY

Hi-Tec Drawing Oil 1755S is suitable for use with most organic hose and seal materials commonly used for petroleum based oils however for advice regarding specific materials contact the material supplier or Hi-Tec Oils.

SAFETY

The measures to be taken to ensure the protection of health and safety at the workplace are described in the Safety Data Sheet (SDS). A SDS is sent at the first delivery and regularly updated.

STORAGE

If the following criteria are adhered to, the product can be stored for at least six months:

Maximum recommended long-term storage temperature: 40°C.

Minimum recommended long-term storage temperature : 0°C.

Keep drums/containers tightly closed when not in use.

Keep drums/containers tightly closed when not in use.

Store containers/drums in a dry and well ventilated area.

TYPICAL CHEMICAL AND PHYSICAL PROPERTIES

Property	Results
Appearance:	Clear amber liquid
Specific gravity @25°C:	0.750 – 0.765
Total Solids:	6 – 8 %



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Available in: 205 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI6-2938

Effective: September 2013

Expires: September 2015

GH319003/1



AUSTRALIAN FAMILY OWNED SINCE 1989

