



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

## PRODUCT DATA SHEET

### EVOLUTION SEMISYN 10W40 SN/CF

#### PRODUCT DESCRIPTION

**Evolution 10W40 SN/CF** is a premium quality high SAPS, API SN/CF engine oil providing increased engine protection through increased oxidation resistance. It is suitable for many types of petrol, diesel, and LPG four stroke engines in passenger cars and trucks, especially European models without catalytic exhaust systems under both severe and varied operating conditions. It is ideal for use in the professional workshop.

**Evolution 10W40 SN/CF** helps reduce engine oil oxidation, giving more protection from piston deposits compared to standard SN engine oils.

Engine cleanliness is also promoted by the increased level of dispersants in **Evolution 10W40 SN/CF**. The special additives inhibit the formation of sludge especially under the constant cold temperature operation of urban motoring.

**Evolution 10W40 SN/CF** is excellent for cold starting as it has good fluidity characteristics, and provides increased engine life as the wear rates for both cams and bearings are decreased compared to less advanced oils.

The high temperature performance of **Evolution 10W40 SN/CF** is also enhanced by the selection of the thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents.

**Evolution 10W40 SN/CF** is suitable for use in both high speed high temperature motorway driving or low temperature stop-and-go driving, and in engines with small clearances.

#### BENEFITS

- Improved oxidation resistance for better sludge control.
- Control of piston deposits for improved engine cleanliness.
- Better wear protection.
- Protection at high temperatures to resist oxidation, nitration and oil thickening.
- Fast flow at cold temperature start up.

#### SPECIFICATIONS

**Evolution 10W40 SN/CF** meets or exceeds the following demanding performance specifications:

API: SN, SM, SL, SJ, SH, CF, CD

ACEA: A3/B4

Mercedes Benz: MB229.1

Renault: RN0700

Volkswagen: VW505.00, VW501.01

Always consult your vehicle owner's manual for the manufacturer's recommendations.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

[www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)

## PRODUCT DATA SHEET

### TYPICAL PROPERTIES

Property	ASTM Method	Results
Density, kg/lit @15°C	ASTM D-1298	0.871
Viscosity @ 100°C cSt	ASTM D-445	14.8
@ 40°C cSt	ASTM D-445	103
Viscosity Index	ASTM D-2270	150
CCS @-25°C	ASTM D-5293	6480
Flash Point (COC) °C	ASTM D-92	232
Pour Point °C	ASTM D-97	-39
Calcium %wt	ICP	0.30
Zinc %wt	ICP	0.11
Phosphorus %wt	ICP	0.10
Nitrogen %wt	-	0.11
TBN mgKOH/g	ASTM D-2896	10.7

**Available in:** Bulk, 1000 Litres, 200 Litres, 20 Litres, 5 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au). Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at [www.hi-tecoils.com.au](http://www.hi-tecoils.com.au)"

**Item code:** HI1-2101

**Effective:** March 2022

MR223013/1



AUSTRALIAN FAMILY OWNED SINCE 1989

