

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

## FAST 2 HIGH PERFORMANCE 2 STROKE

## PRODUCT DESCRIPTION

Fast 2 High Performance 2 Stroke is designed to be used in high performance top tier two stroke motor cycle engines and power tools. It is formulated from a high quality mineral base stock with detergent additives to create a modern low ash lubricant.

Fast 2 High Performance 2 Stroke has consistently given excellent engine cleanliness and freedom from ring sticking under controlled test conditions. Its performance reputation is based upon practical field experience involving the continual development and improvement of the lubricant additive system in high performance motorcycle racing engines.

Fast 2 High Performance 2 Stroke is manufactured with self-mixing solvents and should be used at the fuel/oil ratio recommended by the engine manufacturer. Fast 2 High Performance 2 Stroke may also be used in small to medium sized water-cooled engines, which may not be sensitive to low ash levels. However it should not be used in water-cooled outboard engines.

# **SPECIFICATIONS**

Fast 2 High Performance 2 Stroke meets or exceeds the following demanding performance requirements:

API TC.

JASO FA and FB, ISO-L-EGB.

Always consult the vehicle owner's manual for the manufacturer's recommendations.

### **TYPICAL PROPERTIES**

Property	<b>ASTM Method</b>	Typical Results
Density (kg/Lt) @ 15.0°C	D-1298	0.868
Viscosity (cSt) @ 40°C	D-445	50
Nitrogen Content (% wt)	D-3228	0.02
Calcium Content (% wt)	D-4927	0.04
Ash (% wt)	D-874	0.14

4 Litres and 1 Litre Available in:

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI8 - 2135A

Effective: February 2020

MR022031/1





