



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

FLEETWASH

PRODUCT DESCRIPTION

Fleetwash is a coconut oil based detergent formulation containing inorganic phosphates for the purpose of removing dirt, mud, oil film and road grime from all washable surfaces.

Fleetwash can be used for all road, commercial and recreational vehicles, engines, and under bodies. It can be used on magnesium and alloy wheels, tyres and rubber inserts.

Fleetwash has proved effective in commercial applications, in industrial separation systems, on concrete floors and driveways, building exteriors, windows, and domestic laundries and as a non-solvent hand cleaner.

APPLICATION

Fleetwash may be left to dry on any surface being washed, and it will rinse freely away carrying with it dirt, oil and grime deposits without streaking. It will not promote rust as the solution contains an active rust inhibitor. The solution has an unlimited shelf life in an unopened container, and is biodegradable, beginning to breakdown after dilution. The more diluted the product, the less effective it will be. Prolonged use will not have an adverse effect on rubber, paint, vinyl or fabric. It also works effectively with either hand sprays or pressure washers.

DIRECTIONS FOR USE

- Manual Washing – Dilute with up to 10 parts of clean water, sponge on, allow 3-5 minutes, and then rinse clean with water.
- Low Pressure Spraying - Dilute with up to 10 parts of clean water, spray on, allow 3-5 minutes, and then rinse clean with water.
- High Pressure Spraying – Dilute with up to 15 parts of clean water (up to 20 parts water can also be successful), spray or foam onto surface, allow 3-5 minutes, then pressure rinse with clean water.

PROPERTIES

Fleetwash is a biodegradable cleaning agent, blue in colour, water soluble and non-flammable. It has a pH range in solution of 7.0 - 8.0.

Available in: 200 Litres, 20 Litres, 5 Litres and 1 Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI8-3170

Effective: December 2019

MR912160/1



AUSTRALIAN FAMILY OWNED SINCE 1989

