



PRODUCT DATA SHEET

HEAT TRANSFER OILS

PRODUCT DESCRIPTION

Heat Transfer Oils are high performance fluids intended for use in closed indirect heating installations. They are formulated from highly refined base stocks that are resistant to thermal cracking and chemical oxidation.

Heat Transfer Oils have good heat transfer efficiency and the viscosities are such that they can be pumped readily at both start-up and operating temperatures. The flash point of these fluids will not decrease significantly in service because of the fluid's resistance to thermal cracking at the operating temperatures for which they are recommended.

Heat Transfer Oils are very thermally stable and capable of an extremely long service life without deposit formation or viscosity increase. They demonstrate specific heats and thermal conductivities that provide more rapid heat dissipation.

Heat Transfer Oils are may be used in open, cold-oil sealed and indirect heating and cooling systems in all kinds of industrial processes. **Heat Transfer Oils** have excellent GM Quenchometer (ASTM D-3520) performance.

APPLICATIONS

Heat Transfer Oils can be used in open installations where fuming of the oil could be a problem. Specific application ranges and advice are (temperature range for bulk fluids):

- Closed systems: up to 300°C
- Open systems: up to 160°C

APPLICATION CONSIDERATIONS:

Ideally **Heat Transfer Oils** should not be mixed with other oils since this may impair the excellent thermal and oxidation stability of the **Heat Transfer Oils** and may cause changes in other properties; thus complicating the interpretation of analyses made to determine the fluid's useful life.

If the fluid is used above the recommended maximum temperatures, vapor lock may result unless the system is designed to operate at the higher temperature by pressurizing with an inert gas such as nitrogen. However, at higher temperatures, fluid life will be shortened because the rate of thermal degradation increases markedly as temperatures rise above the recommended limit.

In well-designed systems the temperature of the oil film surrounding the heating element should be about 15°C to 30°C above the bulk oil temperature. If higher than this, the service life of the fluid may be shortened and sludge and coke may be deposited, which would interfere with the heat transfer rates.

As with other mineral oils, **Heat Transfer Oils** should be used only in systems with forced circulation. Systems that depend on convection for circulation of the heat transfer medium do not provide a rapid enough flow to prevent local overheating, resulting in a rapid deterioration of the fluid.

Further, these fluids are not recommended for use in open systems where hot fluid is exposed directly to the air. If hot fluid sprays or escapes from leakage points, it may spontaneously ignite.

Hi-Tec suggests that the equipment manufacturers' recommendations for viscosity grade, performance requirements and general operating conditions should be checked prior to use.



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL PROPERTIES

Property	Units	ASTM Method	Typical Results					
ISO Viscosity	-	-	12	21	25	32	68	90
Product Code (HI6-)	-	-	2872	2876	2877	2873	2880	2874
Density @ 15°C	kg / L	D-1298	834	850	858	871	873	879
Viscosity @ 40°C	cSt	D-445	12	21	25	32	68	90
Viscosity @ 100°C	cSt	D-445	3	4.25	4.5	5.4	8.8	11
Flash Point	°C	-	200	200	200	220	250	260
Spontaneous Ignition Temperature	°C	-	>400	>400	>400	>400	>400	>400
Recommended Temperature Maximum	°C	-	250	300	300	300	300	300

Available in: Bulk, 1000 Litres, 200 Litres and 20 Litres.

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: March 2020

MR023030/1



AUSTRALIAN FAMILY OWNED SINCE 1989

