

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765 Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

KEROSENE

PRODUCT DESCRIPTION

Kerosene is a premium quality kerosene for use in various applications including heating, cooking and refrigeration. It can be used as a lighting fuel, to power engines and also as a solvent for degreasing and other industrial applications.

TYPICAL PROPERTIES

Property	Results
Appearance	Clear, pale yellow/straw to colourless liquid.
Density @ 15°C, kg/L	Typically 0.79
Flash Point, °C	≥ 38
Boiling Point, °C	Typically 150 – 300
Auto-ignition Temperature, °C	> 220

TRANSPORT AND HANDLING

UN No.	1223
Dangerous Goods Class	3, Flammable Liquids
Hazchem Code	3Y
Packaging Group	111

Refer to the Safety Data Sheet for safety instructions prior to handling.

Available in: 200 Litres and 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at <u>www.hi-tecoils.com.au</u>. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI8-3220

Effective: March 2020

MR023040/1



AUSTRALIAN FAMILY OWNED SINCE 1989