

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | **Fax:** (02) 9604 1611 | **Email:** hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

LIMITED SLIP ADDITIVE

PRODUCT DESCRIPTION

Limited Slip Additive is a friction modifier which can be used to supplement sulfur-phosphorous gear oil additives for limited-slip performance.

FEATURES OF LIMITED SLIP ADDITIVE

- Excellent anti-chatter performance.
- Cost effective solution for improving noise, vibration and harshness (NVH) performance.
- Meets the performance requirements of major automotive manufacturers including Ford M2C118A, Arvin Meritor, Dana 40819, Daimler Chrysler MS 5630 and ZF TE-ML 05C, 12C and 16E.

APPLICATION

Limited Slip Additive is a balanced formulation for use in conjunction with various lubricant additives. **Limited Slip Additive** is compatible with GL-5, J2360 and MIL-PRF-2105E gear lubricants.

HOW TO USE

Limited Slip Additive can be used at the following concentrations:

- For limited-slip characteristics 2% 5%
- For Manual transaxles 3% 5%
- For Universal tractor fluids 2% 4%

TYPICAL PROPERTIES

Property	Units	Results
Appearance of test liquid		Amber fluid
Density @ 20 °C	kg/L	0.92
Viscosity @ 100 °C	cSt	9
Phosphorous content	% w/w	1.5
Sulphur content	% w/w	0.8
Nitrogen content	% w/w	1.5

Available in: Bulk, 10 Litres and 200 mls

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI4-4645

Effective: March 2020

MR023011/1





