



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

LONG LIFE COOLANT BLUE

PRODUCT DESCRIPTION

Long Life Coolant Blue is an ethylene glycol based anti-freeze/coolant concentrate incorporating an advanced Organic Acid Technology (OATS) formula with virtually non-depleting organic acid corrosion inhibitors. The product is dyed a distinctive blue colour for ease of identification.

It is silicate free for improved pump life and contains no environmentally harmful nitrates, borates, phosphates, amines or nitrites.

Long Life Coolant Blue is compatible with conventional coolants and can be used for top-up of conventional coolants. If the product is to be mixed with some heavy duty diesel coolants, the user must continue to add SCA's (Supplementary Coolant Additives) for heavy-duty service until the next coolant change-out.

Long Life Coolant Blue satisfies or exceeds many major standards and is recommended for major European, Japanese and US car and heavy-duty diesel engines.

Long Life Coolant Blue can be added directly to the cooling system as a top-up adjustment of the freeze point of the cooling water.

APPLICATION

Long Life Coolant Blue is recommended for use in aluminium alloy petrol powered automotive engines, and in heavy duty diesel and natural gas mobile and stationary engines.

Provided the correct dosage of **Long Life Coolant Blue** is maintained, flush and change the passenger car/light duty commercial vehicle cooling system contents every 5 years or 250,000 km. For heavy-duty diesel engines, **Long Life Coolant Blue** more than doubles the life of conventional coolants to 500,000 km / 6,000 hours / 5 years; at the same time providing excellent protection against cylinder liner cavitation corrosion/erosion.

DOSAGE RATE

Long Life Coolant Blue	Water	Freeze Protection	Boil Protection *
1 part	1 part	-37°C	129°C
1 part	2 parts	-20°C	121°C

* with a 103 kPa radiator pressure cap

Long Life Coolant Blue anti-freeze/coolant must not be used neat to the engine cooling system but diluted up to minimum 33% or maximum 67% with good quality water. The dosage depends on the level of frost protection required and/or the manufacturer's recommendation. For optimum year round protection against freezing, boiling and corrosion, 50% **Long Life Coolant Blue** coolant solution is recommended.

While **Long Life Coolant Blue** is compatible with hard water, the use of soft or deionised water is preferable to minimize scale deposits.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Do not mix **Long Life Coolant Blue** coolant with other coolant products as the extended life benefits will be reduced. If mixed with more than 15% of conventional coolant, treat the cooling system as if it contains the conventional coolant or drain and flush the system and refill with **Long Life Coolant Blue**.

CHANGE-OVER

Always start off with a clean cooling system by using a radiator flush or similar commercial cleaner at the change-over (especially if previously using conventional coolants). After draining the cleaner, flush thoroughly with clean water.

Inspect the cooling system. Make necessary repairs and tighten all hose connections.

The coolant should be changed out at overhaul or 5 years. Always dispose of the used coolant in accordance with local, state and federal guidelines.

Because **Long Life Coolant Blue** is silicate free, the product can be stored for up to 8 years with no problem.

BENEFITS

Advantages of using **Long Life Coolant Blue** include:

- Can be used in most OEM diesel, petrol and natural gas engines allowing one coolant to be inventoried. The product lasts up to 3 times as long as conventional coolants.
- Reduces engine coolant cost by up to 60% over conventional coolants.
- Service life of up to 1,000,000 km for truck engines, and up to 12,000 hours or 6 years (whichever comes first) for machine/commercial engines (when topped up with a once only coolant extender at the end of its initial service life).
- For automotive engines, drain at 250,000 km or 5 years, whichever comes first.
- Contains no silicates or environmentally harmful borates, phosphates, amines or nitrates.
- Hard water deposits and scale from silicate drop out in the cooling system are practically eliminated.
- The low level of total dissolved solids improves water pump seal life and prevents gel formation.
- Excellent heat transfer and superior aluminium protection at high operating temperatures.
- The combination of organic carboxylate inhibitors offers excellent protection against cast iron cylinder liner and block pitting and cavitation corrosion-erosion.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

RECCOMENDATONS

Long Life Coolant Blue is recommended for all heavy duty engines manufactured by Cummins, Caterpillar, Detroit Diesel, Mack-RVI, Mercedes Benz, Scania, MTU, Komatsu and other OEM's.

It is recommended where the following performance levels are cited:

ASTM D-3306 (and D-4656)

ASTM D-4985 (and D-5345)

ASTM D-6210

BS 6580 (British Standard)

UNE 26-361-88/1

FVV Heft R443 (Germany)

NATO S-757

BT-PS-606A (MIL-Belgium)

E/L-1415b (MIL-Italy)

SAE J1034

JIS K2234 (Japan) LLC

JASO M325 (Japan) LLC

Afnor R15-601

Önorm V5123

BR 637

DCEA 615 (MIL-France)

FSD 8704 (MIL-Sweden)

AS/NZS 2108.1:1997 (Australian Standard) Type A

Navistar

Mitsubishi ES-X64216

Honda

Hyundai

MAN 324 (Diesel Engines)

Volvo

Scania (Tech Info. TI 02-98)

Mercedes-Benz Sheet 325.3

Mack-RVI

Caterpillar EC-1

Cummins 90 T8-4

Detroit Diesel/Perkins

Komatsu

General Motors GM 6277M

General Motors GM 1899M

Ford WSS-M97B44-C

Volkswagen VW TL774D

Audi/SEAT/Skoda

ISUZU

BMW N600 69.0

SAAB

DAF-Leyland 74001

Mazda MES 121C

Toyota TS K2601 G

Daihatsu

Subaru

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property

Colour

pH (neat)

Ethylene Glycol content (% wt)

g/L typical

Reserve Alkalinity, mL (pH 5.5)

Density (g/mL) @ 20°C

Boiling Point (°C)

Freezing Point (max °C)

(50% vol solution)

Typical results

Blue

6.0 – 9.0

93.0

1060

5

1.11 - 1.14

172

< -37



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

SAFETY AND HANDLING

This product contains ethylene glycol and is a Schedule 5 poison.

Read the Safety Data Sheet (SDS) before opening the container and using the product.

Available in: 200 Litres and 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI8-3230

Effective: February 2020

MR022082/1



AUSTRALIAN FAMILY OWNED SINCE 1989

