

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

DUCT DATA SHEET

MOLY LITH EP2

PRODUCT DESCRIPTION

MOLY LITH EP2 is a premium lithium soap thickened grease formulated with an advanced extreme pressure (EP) and anti-wear (AW) additive technology. It contains Molybdenum Disulphide to provide extra protection against wear.

MOLY LITH EP2 is a multi-service grease suitable for use in both automotive and industrial applications. In addition to its EP and anti-wear characteristics it also provides a high level of oxidation, rust and water washout protection. MOLY LITH EP2 has demonstrated outstanding performance with regard corrosion protection, low temperature pumpability and high temperature service.

The state-of-the-art equipment and procedures employed to manufacture **MOLY LITH EP2** grease provide it with a high degree of mechanical and storage stability. It resists breakdown under high mechanical stress, and in stress storage it will maintain its consistency.

BENEFITS

- Reduced wear under high shock loads
- Superior protection against rust and corrosion
- Excellent mechanical stability
- Lead, chlorine and nitrite free
- Excellent resistance to water washout
- Good pumpability in centralised systems
- Outstanding storage stability

RECOMMENDATIONS

MOLY LITH EP2 is recommended for use in most types of automotive and industrial applications including heavy duty service where high loads are encountered. It is suitable for rolling element bearings, plain bearings, gears and couplings. Because of its outstanding corrosion and water resistant properties it is particularly suitable where water ingress is present such as underground tunneling or mining and ore crushing plants.

The recommended operating temperature range for MOLY LITH EP2 is from -20 °C to 140 °C. However it can endure higher temperatures for short periods or if the lubrication frequency is increased.

Hi-Tec suggests that the equipment manufacturers' recommendations for grade, performance requirements and general operating conditions should be checked prior to use.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

RODUCT DATA SHEET

TYPICAL PROPERTIES

Property Method Results **Appearance Smooth Grease** Colour Grey/Black 2 **NLGI** Soap Type Lithium **Blend Mineral Oils** Base Oil IP50 Worked Penetration 265 to 295 Dropping Point °C 185 min IP132 Oil Separation % IP121 5 max Copper Corrosion **IP112 Pass** Resistance to Corrosion Emcor IP220 0:0 Water Washout at 39°C, % **ASTM D1264** 3 4-Ball Weld, Kg/f IP239 315 Operating Temperature Range °C -20 to 140 Solids % -

Available in: Bulk, 180kg, 20kg and 450 gr

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI7-1015

Effective: March 2020

MR023013/1











Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 1 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

Product name: Moly Lith Grease

1. COMPANY DETAILS AND PRODUCT IDENTIFICATION

COMPANY: Hi-Tec Oil Traders Pty Ltd. (ABN 28 053 837 362)

ADDRESS: PO Box 322 Castle Hill NSW 1765

5 Tarlington Place, Smithfield NSW 2164

TELEPHONE NUMBER: 1300 796 009

FAX NUMBER: (02) 9604 1611

EMERGENCY TELEPHONE NUMBER: 1300 796 009

PRODUCT NAME: Moly Lith Grease

OTHER NAMES: None

MANUFACTURER'S PRODUCT CODE: HI7-1015

USE: Lithium soap, multipurpose grease containing Molybdenum Disulphide.

ADDITIONAL INFORMATION: Refer to Product Information Sheet for additional information.

OTHER INFORMATION: Visit our website: www.hi-tecoils.com.au

Email: hitecoils@hi-tecoils.com.au

2. HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: NON-HAZARDOUS

NON-DANGEROUS GOODS

Hazard classification according to GHS Classification.

Dangerous goods classification according to Australian Dangerous Goods Code.

SIGNAL WORD (S): None

IRRITANCY OF PRODUCT: Not classified as an irritant.

SENSITISATION OF PRODUCT: Not known to be a sensitiser.

TERATOGENICITY: No teratogenic effects known.

OTHER INFORMATION: Used greases may contain harmful impurities that have accumulated during use. The

concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used oils should be handled with caution and

skin contact avoided as far as possible.









Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

Y DATA SH

Page 2 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

3. COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTICS: Grease

INGREDIENTS:-

CHEMICAL ENTITY CAS NO **PROPORTION** Distillates (petroleum), hydrotreated heavy napthenic 64742-52-5 70-100% Phosphorodithioic acid. O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts 85940-28-9 1 - 2.5%Molybdenum Disulphide 1317-33-5 < 1% Graphite 7782-42-5 < 1% Calcium Carbonate 1317-65-3 < 1% Ingredients determined to be non-hazardous To 100%

4. FIRST AID MEASURES

GENERAL INFORMATION: You should call the Poisons Information Centre on 13 11 26 from anywhere in

Australia (0800 764 766 in New Zealand) if you feel that you may have been

poisoned, burned or irritated by this product. Have this SDS with you when you call.

INHALATION: No specific recommendations. If throat irritation or coughing persists, proceed as

> follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get

medical attention if any discomfort continues.

INGESTION: No specific recommendations. If throat irritation or coughing persists, proceed as

follows. Rinse mouth. Get medical attention if any discomfort continues.

SKIN CONTACT: No specific recommendations. Rinse with water. Get medical attention if any

discomfort continues.

Remove any contact lenses and open eyelids wide apart. Rinse with water. Get EYE CONTACT:

medical attention if any discomfort continues.

FIRST AIDERS: Use protective equipment appropriate for surrounding materials.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

The severity of the symptoms described will vary dependent on the concentration and GENERAL INFORMATION:

the length of exposure.

INHALATION: No specific symptoms known.

INGESTION: No specific symptoms known. May cause discomfort if swallowed.

SKIN CONTACT: Prolonged contact may cause dryness of the skin.

EYE CONTACT: No specific symptoms known. May be slightly irritating to eyes.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

Y DATA SH

Page 3 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

4. FIRST AID MEASURES (CONT)

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

NOTES TO PHYSICIAN: Treat symptomatically.

SPECIAL TREATMENTS: No special treatment required.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use

fire-extinguishing media suitable for the surrounding fire.

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS: None known.

HAZARDOUS COMBUSTION PRODUCTS: Thermal decomposition or combustion products may include the following

substances:

Harmful gases or vapours. Carbon dioxide (CO₂). Carbon monoxide (CO). Oxides of

sulphur. Oxides of phosphorus. Oxides of nitrogen.

ADVICE FOR FIREFIGHTERS

PROTECTIVE ACTIONS: Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat

with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate SPECIAL PROTECTIVE EQUIPMENT:

protective clothing. Firefighter's clothing conforming to European standard EN469

(including helmets, protective boots and gloves) will provide a basic level of

protection for chemical incidents.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: No specific recommendations. For personal protection, see Section 8.

ENVIRONMENTAL PRECAUTIONS: Avoid discharge into drains or watercourses or onto the ground.

METHODS FOR CONTAINMENT

& CLEANING UP: Reuse or recycle products wherever possible. Collect spillage with a shovel and

broom or similar and reuse if possible. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of contents/container in accordance

with national regulations.

REFERENCE TO OTHER SECTIONS: For personal protection, see Section 8. For waste disposal, see Section 13.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

Y DATA SH

Page 4 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

7. HANDLING AND STORAGE

ADVICE ON GENERAL OCCUPATIONAL

HYGIENE:

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and

animal feeding stuffs. Keep container tightly closed when not in use.

HYGIENE MEASURES: Wash promptly if skin becomes contaminated. Take off contaminated clothing.

Wash contaminated clothing before reuse.

STORAGE PRECAUTIONS: Store away from incompatible materials (see Section 10). No specific

recommendations.

Unspecified storage. STORAGE CLASS:

SPECIFIC END USES: The identified uses for this product are detailed in Section 1.2

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

Distillates (petroleum), hydrotreated heavy naphthenic: Short-term exposure limit (15-minute): WEL 10 mg/m³ mist

Molybdenum Disulphide

Long-term exposure limit (8 hour TWA): WEL 10 mg/m³ Long-term exposure limit (15-minute): WEL 20 mg/m³

Long-term exposure limit (8 hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8 hour TWA): WEL 4 mg/m³ respirable dust

Calcium Carbonate

Long-term exposure limit (8 hour TWA): WEL 10 mg/m³ inhalable dust Long-term exposure limit (8 hour TWA): WEL 4 mg/m³ respirable dust

WEL = Workplace Exposure Limit

EXPOSURE CONTROLS

ENGINEERING CONTROLS: No specific ventilation requirements.

EYE/FACE PROTECTION: No specific eye protection required during normal use. Large Spillages: Eyewear

complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

HAND PROTECTION: No specific hand protection recommended. Large Spillages: Wear protective gloves.

SKIN/BODY PROTECTION: Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENE MEASURES: Wash after use and before eating, smoking and using the toilet. Do not eat, drink or

smoke when using this product.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 5 of 15 Issue Date: 30 March 2022 Moly Lith Grease

Version: 4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION (CONT)

RESPIRATORY PROTECTION: No specific recommendations. Provide adequate ventilation. Large Spillages: If

ventilation is inadequate, suitable respiratory protection must be worn.

ENVIRONMENTAL EXPOSURE CONTROLS: Not regarded as dangerous for the environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Grease

COLOUR: Grey to black

ODOUR: Almost odourless

ODOUR THRESHOLD: No information available

pH: Not applicable

MELTING POINT: >180°C

INITIAL BOILING POINT AND RANGE: No information available

FLASH POINT: >200°C Pensky-Martens closed cup. Information given is applicable to the major

ingredient

EVAPORATION RATE: No information available

EVAPORATION FACTOR: No information available

FLAMMABILITY (SOLID, GAS): No information available

UPPER / LOWER FLAMMABILITY OR

EXPLOSIVE LIMITS: No information available

OTHER FLAMMABILITY: No information available

VAPOUR PRESSURE: No information available

VAPOUR DENSITY: No information available

RELATIVE DENSITY: Approximately 0.89 @ 25°C

BULK DENSITY: No information available

SOLUBILITY(IES): Insoluble in water.

PARTITION COEFFICIENT: No information available

AUTO-IGNITION TEMPERATURE: No information available









Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

Page 6 of 15 Issue Date: 30 March 2022 Moly Lith Grease

Version: 4

9. PHYSICAL AND CHEMICAL PROPERTIES (CONT)

DECOMPOSITION TEMPERATURE: No information available

150 cSt @ 40°C. Information given is applicable to the major ingredient VISCOSITY:

EXPLOSIVE PROPERTIES: Not considered to be explosive

EXPLOSIVE UNDER THE INFLUENCE OF

A FLAME: Not considered to be explosive

OXIDISING PROPERTIES: Not applicable

10. STABILITY AND REACTIVITY

REACTIVITY: No test data specifically related to reactivity available for this product or its

ingredients.

CHEMICAL STABILITY: Stable at normal ambient temperatures and when used as recommended. Stable under

the prescribed storage conditions.

HAZARDOUS REACTIONS: No potentially hazardous reactions known.

CONDITIONS TO AVOID: Avoid excessive heat for prolonged periods of time.

INCOMPATIBLE MATERIALS: Avoid contact with the following materials: Strong oxidising agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Does not decompose when used and stored as recommended. Thermal decomposition

or combustion products may include the following substances: Harmful gases or

vapours. Carbon dioxide (CO₂). Carbon monoxide (CO).

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL EFFECTS: Not regarded as a health hazard under current legislation.

ACUTE TOXICITY - ORAL

Notes (oral LD₅₀): Based on available data the classification criteria are not met.

ACUTE TOXICITY - DERMAL

Notes (dermal LD₅₀): Based on available data the classification criteria are not met.

ACUTE TOXICITY - INHALATION

Based on available data the classification criteria are not met. Notes (inhalation LC_{50}):

SKIN CORROSION/IRRITATION

Animal data: Based on available data the classification criteria are not met.









Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 7 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

11. TOXICOLOGICAL INFORMATION (CONT)

SERIOUS EYE DAMAGE/IRRITATION

Serious eye damage/irritation: Based on available data the classification criteria are not met.

RESPIRATORY SENSITISATION

Respiratory sensitisation: Based on available data the classification criteria are not met.

SKIN SENSITISATION

Skin sensitisation: Based on available data the classification criteria are not met.

GERM CELL MUTAGENICITY

Genotoxicity - in vitro: Based on available data the classification criteria are not met.

CARCINOGENICITY

Carcinogenicity: Based on available data the classification criteria are not met.

IARC carcinogenicity: None of the ingredients are listed or exempted.

REPRODUCTIVE TOXICITY

Reproductive toxicity – fertility: Based on available data the classification criteria are not met.

Reproductive toxicity – development: Based on available data the classification criteria are not met.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

ASPIRATION HAZARD

Aspiration hazard: Not relevant. Solid.

GENERAL INFORMATION: No specific health hazards known. The severity of the symptoms described will vary

dependent on the concentration and the length of exposure.

INHALATION: No specific symptoms known.

INGESTION: No specific symptoms known. May cause discomfort if swallowed.

SKIN CONTACT: Prolonged contact may cause dryness of the skin.

EYE CONTACT: No specific symptoms known. May be slightly irritating to eyes.

ROUTE OF ENTRY: Ingestion, Inhalation, Skin and/or eye contact

TARGET ORGANS: No specific target organs known.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 8 of 15 Issue Date: 30 March 2022 Moly Lith Grease

Version: 4

11. TOXICOLOGICAL INFORMATION (CONT)

TOXICOLOGICAL INFORMATION ON INGREDIENTS

Distillates (petroleum), hydrotreated heavy napthenic

ACUTE TOXICITY - ORAL

Notes (oral LD_{50}): OECD 401 > 5000 mg/kg, Oral, Rat.

ACUTE TOXICITY - DERMAL

Notes (dermal LD_{50}): OECD 402 > 5000 mg/kg, Dermal, Rabbit.

ACUTE TOXICITY - INHALATION

Notes (dermal LC_{50}): OECD 403 > 5.53 mg/l, 4 hours, Dust/Mist, Rat.

SKIN CORROSION/IRRITATION

Skin corrosion/irritation: Not irritating.

SERIOUS EYE DAMAGE/IRRITATION

Serious eye damage/irritation: Not irritating.

SKIN SENSITISATION

Skin sensitisation: Not sensitising.

CARCINOGENICITY

Carcinogenicity: Based on available data the classification criteria are not met.

Molybdenum Disulphide

ACUTE TOXICITY - INHALATION

Notes (dermal LC₅₀): > 2,820 mg/m³, 4 hours, Dust/Mist, Inhalation, Rat.

Graphite

ACUTE TOXICITY - ORAL

Notes (oral LD_{50}): LD_{50} 2,000 mg/kg, Oral, Rat.

ACUTE TOXICITY - INHALATION

Notes (inhalation LC_{50}): $LC_{50} > 2,000 \text{ mg/m}^3$, Inhalation, Rat.

Calcium Carbonate

ACUTE TOXICITY - ORAL

Notes (oral LD_{50}): $LD_{50} > 5000$ mg/kg, Oral, Rat.

ATE oral (mg/kg): 5000.0

ACUTE TOXICITY - DERMAL

Notes (dermal LD_{50}): $LD_{50} > 5000$ mg/kg, Dermal, Rat.









Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 9 of 15 Issue Date: 30 March 2022 Moly Lith Grease

Version: 4

11. TOXICOLOGICAL INFORMATION (CONT)

SKIN CORROSION/IRRITATION

Animal data: Not irritating.

SERIOUS EYE DAMAGE/IRRITATION

Serious eye damage/irritation: Not irritating.

RESPIRATORY SENSITISATION

Respiratory sensitisation: No data available.

12. ECOLOGICAL INFORMATION

ECOTOXICITY: Not regarded as dangerous for the environment. However, large or frequent spills may

have hazardous effects on the environment.

TOXICITY: Based on available data the classification criteria are not met.

ECOLOGICAL INFORMATION ON INGREDIENTS:

Distillates (petroleum), hydrotreated heavy napthenic

ACUTE AQUATIC TOXICITY:

Acute Toxicity – Fish LC_{50} , 96 hours: >100 mg/l Acute Toxicity – Aquatic Invertebrates EC_{50} , 96 hours: >10,000 mg/l EC_{50} , 72 hours: >100 mg/l

CHRONIC AQUATIC TOXICITY:

Chronic Toxicity – Aquatic Invertebrates NOEC, 21 days: 10 mg/l

Phosphorodithioic acid. O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts

ACUTE AQUATIC TOXICITY:

Acute Toxicity – Fish LC₅₀, 96 hours: 4.5 mg/l, Oncorhynchus mykiss (Rainbow trout)

NOEC, 96 hours: 1.8 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute Toxicity – Aquatic Invertebrates EC₅₀, 48 hours: 5.4 mg/l, Daphnia magna

NOEC, 48 hours: <1 mg/l, Daphnia magna

Acute Toxicity – Aquatic Plants LC₅₀, 96 hours: 2.1 mg/l, Scenedesmus subspicatus

Calcium Carbonate

ACUTE AQUATIC TOXICITY:

Acute Toxicity – Fish LC₅₀, 96 hours: >10,000 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute Toxicity – Aquatic Invertebrates EC₅₀, 48 hours: >1,000 mg/l, Daphnia magna

Acute Toxicity – Aquatic Plants EC₅₀, 72 hours: >200 mg/l, Scenedesmus subspicatus

PERSISTENCE AND DEGRADABILITY:

Persistence and degradability The degradability of the product is not known.









Ph: 1300 796 009 | **Fax:** (02) 9604 1611 | **Email:** hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 10 of 15 Issue Date: 30 March 2022 Moly Lith Grease

Version: 4

12. ECOLOGICAL INFORMATION (CONT)

<u>Distillates (petroleum), hydrotreated heavy napthenic</u>

Biodegradation Inherently biodegradable.

Phosphorodithioic acid. O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts

Persistence and degradability Not readily biodegradable.

Calcium Carbonate

Persistence and degradability The product contains only inorganic substances which are not biodegradable.

BIOACCUMULATIVE POTENTIAL: No data available on bioaccumulation.

PARTITION COEFFICIENT: No information available

ECOLOGICAL INFORMATION ON INGREDIENTS:

Distillates (petroleum), hydrotreated heavy napthenic

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water-solubility of

this product.

Partition coefficient log Pow: 2 to 6

Calcium Carbonate

Partition coefficient: Not applicable

MOBILITY IN SOIL: No data available.

ECOLOGICAL INFORMATION ON INGREDIENTS:

Distillates (petroleum), hydrotreated heavy napthenic

Mobility: Mobile

RESULTS OF PBT & vPvB ASSESSMENT

ECOLOGICAL INFORMATION ON INGREDIENTS:

Calcium Carbonate

Results of PBT and vPvB assessment: This product does not contain any substances that are classified as PBT or vPvB.









Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

SAFETY DATA SHEET

Page 11 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

12. ECOLOGICAL INFORMATION (CONT)

OTHER ADVERSE EFFECTS: None known.

13. DISPOSAL CONSIDERATIONS

GENERAL INFORMATION: The generation of waste should be minimised or avoided wherever possible. Reuse or

recycle products wherever possible. This material and its container must be disposed

of in a safe way.

DISPOSAL METHODS: Dispose of surplus products and those that cannot be recycled via a licensed waste

disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of the local water authority.

14. TRANSPORT INFORMATION

ROAD & RAIL TRANSPORT:

ADG REQUIREMENT Not classified as a Dangerous Good according to the Australian Code for the

Transport of Dangerous Goods by Road and Rail.

MARITIME TRANSPORT:

IMO/IMDG REQUIREMENT

Not classified as a Dangerous Good according to the criteria of the International

Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT:

ICAO/IATA REQUIREMENT

Not classified as a Dangerous Good according to the criteria of the International

Maritime Air Transport Association (IATA) Dangerous Goods Regulations for

transport by air.

15. REGULATORY INFORMATION

POISON SCHEDULE: Not scheduled.

PACKING & LABELLING: No special packaging or labelling requirements.

AUSTRALIAN INVENTORY STATUS: All components are listed or exempted.









Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

DATA SH

Page 12 of 15 Issue Date: 30 March 2022 Moly Lith Grease Version: 4

16. OTHER INFORMATION

CONTACT PERSON/POINT:

General Manager 1300 796 009

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

LITERATURE REFERENCES:

- * NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
- * Safework Australia: 2016 Code of Practice for the Preparation of Safety Data Sheets for Hazardous Substances.
- * NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
- * NOHSC: 10005 List of Designated Hazardous Substances.
- * NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
- * NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
- * NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
- * NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
- * NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
- * NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.
- * SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
- * ADG: Australian Dangerous Goods Code
- * MSDS of component materials.

LAST CHANGE:

Supercedes document issued: 11 January 2018

Reason/s for revision: Minor editorial adjustments to comply with GHS requirements.

MR223003/1

END OF SDS



