



PRODUCT DATA SHEET

MULTITRANS LV

PRODUCT DESCRIPTION

MULTITRANS LV is a full synthetic automatic transmission fluid specially formulated to meet the requirements of modern North American, European and Asian vehicles with a fuel economy focus. It is suitable for use where the Ford WSS-M2C949-A (ULV) performance level is called for.

MULTITRANS LV has exceptional oxidative resistance, anti-wear performance and frictional stability. It provides excellent anti-rust properties and sludge and varnish control and its multivehicle applicability allows for reduction of inventory of transmission fluids. The lower viscosity of this fluid promotes better fuel economy whilst the advanced chemistry maintains the excellent frictional and anti-shudder characteristics required of modern vehicle transmissions.

MULTITRANS LV may be used for long drain service in many European commercial vehicle applications. It may also be used in power steering units for many cars, light commercial vehicles and tractors except where specialist fluids are recommended e.g. Honda, Mercedes-Benz, SAAB.

BENEFITS

- Maintains the performance of new and enhances the performance of older transmissions.
- Lower viscosity provides less friction and promotes better fuel economy.
- Provides consistent shift performance to allow for longer service intervals.
- Extends transmission fluid life and resists fluid breakdown at higher operating temperatures.
- Provides excellent oxidative stability under severe conditions.
- Provides friction stability and durability combined with excellent wear protection
- Excellent durability for taxis, vehicles used for towing and other hard working applications.
- Reduces sludge and varnish build up.
- Protects transmission gears and allows them to operate smoothly.
- Maintains lubricity.
- Flows well for cold start-up.

SPECIFICATIONS

MULTITRANS LV meets or exceeds the following demanding performance requirements:

Aisin Warner AW-1

Audi G 052 533; G 055 005-A1, -A2; G 055 162; G 055 540-A2; G 060 162-A1, -A2, -A6

Bentley P/N PY112995PA

BMW P/N 83 22 0 142 516; 83 22 0 397 114; 83 22 2 305 396/397; 82 22 2 152 426; 83 22 2 289 720; 83 22 2 163 514; 83 22 2 355 599; ATF 3+

Chrysler MB236.12; P/N 05127382AA; 68043742AA; 68157995AA/AB; 68218925AA

Daimler MB236.12; .14; .15; .16; .17; .41

Dodge MB236.12; P/N 05127382AA; 68043742AA; 68157995AA/AB; 68218925AA

Ford P/N XT-10-QLV (LV); XT-6-QSP/DSP (SP); MERCON LV; SP, WSS-M2C949-A (ULV)

GM AW1; VI; P/N 88863400; 88863401

GMC AW1; VI; P/N 88863400; 88863401

Honda DW-1; ATF Type 3 (08200-916-A); ATF Type 3.1 (08200-9017)

Hyundai NWS-9638 T-5; SP-IV; SPH-IV; SP-IV-M; SP-IV-RR; P/N 040000C90SG

Infinity Matic S; Matic W

Jaguar 02JDE 26444; Fluid 8432

JASO 1A LV

Jeep MB236.12; P/N 05127382AA; 68043742AA; 68157995AA/AB; 68218925AA

JWS 3324

Kia NWS-9638 T-5; SP-IV; SPH-IV; SP-IV-M; SP-IV-RR; P/N 040000C90SG





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Land Rover P/N TYK500050; P/N 023288/023289; LR0022460:LV
Lexus WS; JWS 3324; Scion FZ
Lincoln P/N XT-10-QLV (LV); XT-6-QSP/DSP (SP); MERCON LV; SP
Maserati P/N 231603
Mazda FZ; FW 6A EL; FW 6AX EL
Mercedes MB 236.12, .14, .15, .16, .17, .41
Mercury P/N XT-10-QLV (LV); XT-6-QSP/DSP (SP); MERCON LV; SP
Mini P/N 83 22 0 142 516; 83 22 0 397 114; 83 22 2 305 396/397; 82 22 2 152 426; 83 22 2 289 720; 83 22 2 163 514; 83 22 2 355 599; ATF 3+
Mitsubishi J3; Dia Queen ATF-PA Fluid; SP-IV, ATF-MA1
Nissan Matic S; Matic W
Opel AW1; VI; P/N 88863400; 88863401
Porsche P/N 000 043 304 00
Saab P/N 93 165 147 - AW-1
Saturn AW1; VI; P/N 88863400; 88863401
Scion WS; JWS 3324; Scion FZ
Shell, 3353; 134; M-1375.4; L12108
Toyota WS; JWS 3324; Scion FZ
Volkswagen G 052 533; G 052 540; G 055 005-A1, -A2; G 055 162; G 055 540-A2; G 060 162-A1, -A2
Volvo P/N 31256774; 31256775
ZF Lifeguard Fluid 6; 8; 9.

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

TYPICAL PROPERTIES

Property	Results
Colour	Red
Specific Gravity @ 15°C (g/ml)	0.859
Brookfield cP @ -40°C	10,600
Viscosity @ 100°C (cSt)	6.1
Viscosity @ 40°C (cSt)	30.1
Viscosity Index	156
Pour Point (°C)	-21
Flash Point PMCC (°C)	>200

Available in: Bulk, 1000 Litres, 200 Litres, 60 Litres, 20 Litres and 5 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI3-2672

Effective: August 2024

MR428012/1



AUSTRALIAN FAMILY OWNED SINCE 1989

