



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

MULTITRANS PLUS SYN ATF

PRODUCT DESCRIPTION

MULTITRANS PLUS SYN ATF is a premium full synthetic automatic transmission fluid. It is OEM approved by ZF Friedrichshafen AG to the ZF TE-ML 14C and ZF TE-ML 20C specifications and by Voith Turbo GmbH & Co. to the Voith 55.6336.XX (G1363) specification for use in the transmissions of North American, European and Asian cars, buses, trucks and industrial equipment.

The ZF TE-ML 14C performance level allows oil and filter change intervals up to 120,000 km or two years in ZF Ecomat powershift transmissions in buses. For trucks and off road equipment, this specification allows for oil and filter change intervals up to 1500 hours/1 year under normal service conditions or 1000 hours/1 year under severe conditions. The ZF TE-ML 20C performance level allows oil and filter change intervals up to 120,000 kms or two years in ZF Ecolife powershift transmissions in buses.

The Voith 55.6336.XX (G1363) approval provides for an extended service interval (i.e. up to 120,000 km distance) in Voith DIWA transmissions.

MULTITRANS PLUS SYN ATF has exceptional oxidative resistance, anti-wear performance and frictional stability. It provides excellent anti-rust properties and sludge and varnish control. Its multi-vehicle applicability allows reduction of inventory of transmission fluids.

MULTITRANS PLUS SYN ATF also meets the Ford Mercon[®] V, Allison C-4, JASO 1-A, MAN 339 V1 and MAN 339 Z1, and Volvo 97340 and 97341, and ZF TE-ML 14A and 14B requirements. It is suitable for use in equipment requiring GM Dexron[®] IIIH and Ford Mercon fluids.

CHARACTERISTICS

OUTSTANDING COLD FLOW PROPERTIES

Allows for rapid oil flow to all critical transmission components (i.e. torque converters, friction plates, planetary wheels and brake bands). More responsive and comfortable gear shifts. Minimizes 'shift shock' when gear shifts occur at low temperature. Reduced torque loss increases efficiency leading to fuel savings potential. Less fuel consumption means lower emissions.

OPTIMISED FRICTION CHARACTERISTICS

Smoother gear shifts at all ambient temperatures and load conditions. Consistent frictional properties improve driver comfort. Very long anti-shudder durability for comfortable gear changes without noise, vibration or harshness. Avoids foaming tendencies in transmissions so that full-bodied lubricant is maintained to all surfaces requiring lubrication.

EXCELLENT THERMAL AND OXIDATIVE STABILITY

Viscosity change with usage remains minimal helping prevent deposits and oil thickening – this extends transmission life. Excellent transmission cleanliness under high temperature and high load conditions permits extended oil drain intervals and decreased servicing.

SPECIFICATIONS

MULTITRANS PLUS SYN ATF is specifically designed to meet the ZF TE-ML 14C and ZF TE-ML 20C transmission requirements: ZF Registration No. ZF001669.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

MULTITRANS PLUS SYN ATF will provide suitable performance in numerous passenger cars applications including:

AE, Aisin Warner, Audi, BMW, Chrysler, Daimler, Ford Mercon, GM Dexron, Honda, Hyundai, Jaguar, JASO, JATCO, JWS, Kia, Mazda, Mercedes Benz, Mitsubishi, Nissan, Rover, Saab, Subaru, Toyota, Volvo, VW and ZF; as well as commercial applications including Allison, MAN, Voith and MB (see Hi-Tec MULTITRANS PLUS SYN ATF Part B for a full list).

* Note: Hi-Tec MULTITRANS PLUS SYN ATF is not suitable for use with Continuously Variable Transmissions, Dual Clutch Transmissions or Ford Type F applications.

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property	ASTM Method	Results
Colour	Visual	Red
Density (kg/Lt) @ 15°C	D-1298	0.838
Viscosity (cSt) @ 40°C	D-445	36.45
@ 100°C	D-445	7.6
Viscosity Index	D-2270	184
Brookfield (cP) @ -40°C	D-2983	7,510
Pour Point (°C)	D-97	-50
Flash Point (°C)	D-92	226
Foam	D-892	Pass
Rust Protection	D130, 665A	Pass
FZG, Fail Load	DIN 513554	>12

Available in: Bulk, 1000 Litres, 200 Litres, 60 Litres 20 Litres and 10 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI3-2677

Effective: August 2019

MR918080/1



AUSTRALIAN FAMILY OWNED SINCE 1989

