

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

DUCT DATA SHEET

PREMIER 15W/50 SM

PRODUCT DESCRIPTION

Premier 15W/50 SM is the ultimate in protection and performance designed for workshop or home service. This premium quality engine oil is made using the latest synthetic technology base oils. It meets or exceeds the API SM/CF specifications and is suitable for most types of petrol and four stroke diesel engines including engines with small clearances and those operating under the most severe and varied operating conditions, such as high temperature motorway driving or low temperature stop-and-go driving. Premier 15W/50 SM is ideal for cold starting situations due to its excellent low temperature fluidity characteristics. Its level of dispersant and detergent additives contributes to the engine cleanliness under all service conditions. Special additives inhibit the formation of sludge especially under the constant cold temperature operation of urban motoring. The high temperature performance Premier 15W/50 SM is enhanced by the selection of thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents.

BENEFITS

- Fast flow at cold temperature starting.
- Protection for high temperatures.
- Protection from piston deposits.
- Cleaner engines.

SPECIFICATIONS

Premier 15W/50 SM meets or exceeds the following demanding performance requirements:

API: SM, SL, SJ, SH, CF, CD

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property	ASTM Method	Results
Density @15°C	D-1298	0.877
Viscosity (cSt) @ 100°C	D-445	19.0
@ 40°C	D-445	160
Viscosity Index	D-2270	135
Flash Point; COC (°C)	D-92	225
Pour Point (°C)	D-97	-27

Available In: Bulk, 1000 Litres, 200 Litres, 20 Litres, 5 Litres and 1 Litre

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hitecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI1-2096

Effective: July 2019

MR917071/1





