



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

PREMIER SN/CF 15W/40

PRODUCT DESCRIPTION

Premier SN/CF 15W/40 is the ultimate lubricant for use in the professional workshop to provide engine protection and performance. It meets the API SN and CF requirements and is suitable for most types of petrol and four stroke engines, especially those newer engines with smaller clearances. It performs superbly under the most severe and varied of operating conditions, such as high temperature motorway driving and low temperature stop-and-go city driving.

Premier SN/CF 15W/40 is a premium quality engine oil made using the latest premium technology base oils. Its high temperature performance is enhanced by the use of thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents.

The level of dispersants and detergents in **Premier SN/CF 15W/40** maintains the engine in a much cleaner condition under all service conditions. These special additives inhibit the formation of sludge, especially under the constant cold temperature operation of urban motoring.

Premier SN/CF 15W/40 has excellent cold crank starting properties with ideal fluidity characteristics and provides increased engine life, as the wear rates associated with this high quality engine oil are decreased by approximately 25% for cams and 2% for bearings over the API SL grade. **Hi-Tec Premier SN/CF 15W/40** contributes to 13% less piston deposits with improved oxidation resistance when tested under the Sequence III test methods compared to the older SL grade engine oil.

SPECIFICATIONS

Premier SN/CF 15W/40 meets or exceeds the following demanding performance requirements:

API: SN, SM, SL, SJ, SH, CF, CD

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

TYPICAL PROPERTIES

Property	ASTM Method	Results
Density (kg/Lt) @15°C	D-1298	0.871
Viscosity (cSt) @ 100°C	D-445	14.22
@ 40°C	D-445	112.58
Viscosity Index	D-2270	128
Flash Point; COC (°C)	D-92	214
Pour Point (°C)	D-97	-24

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 10 Litres, 5 Litres and 1 Litre



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

“Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au”

Item Code: HI1-2124

Effective: July 2019

MR9170011/1



AUSTRALIAN FAMILY OWNED SINCE 1989

