



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

RADIATOR FLUSH

PRODUCT DETAILS

Radiator Flush is an environmentally safe and biodegradable cooling system rejuvenator that uses the latest technology to remove rust scale, dirt and debris from radiators, water pumps, water jackets, engine blocks and heads to totally restore and revitalize the cooling system. **Radiator Flush** contains a special blend of additives and surfactants that detach rust, mill scale and debris that has built up over time and suspends them until being drained. It is a non-acidic, non-toxic cleaner safe for all systems.

Radiator Flush is safe on joints, rubbers, seals and gaskets and is suitable for all cars, trucks, tractors and all applications where radiator flushing is required.

DIRECTIONS FOR USE

With the engine cold, remove the radiator cap. Place a large container or pan under the radiator drain to capture the old coolant. Carefully unscrew the drain plug and let the old coolant drain out into the pan. Once the old coolant has drained, replace the drain plug. Fill the radiator with fresh water and turn the engine on. Run the engine until it reaches operating temperature, then allow the engine to cool down.

Repeat the draining process and once the water has drained out, close the radiator drain. Refill the system with tap water and add the **Radiator Flush**. Reinstall the radiator cap and run the engine for about 30 minutes. Allow to cool then repeat the draining process. Keeping the bottom plug open, continue adding fresh water into radiator and flush until clean water emerges, then replace the plug. The system is now flushed.

Add distilled water and fresh coolant to the radiator and circulate for a few minutes at operating temperature whilst observing the water level. Top up if necessary before placing the radiator cap.

USAGE

Under normal usage the 300 mL of **Radiator Flush** is sufficient to clean standard automotive radiators. Larger radiators may require additional dosage. The efficiency of the product is also dependant on the condition of the radiator and flushing technique.

Always consult your vehicle owner's manual for the manufacturer's recommendations.

WORKABILITY

Radiator Flush contains active constituents that will penetrate and loosen hard deposits and rust residues enabling them to break away and float thus facilitating easy removal by flushing. The product also contains additives that will not only clean the interior of radiator but also deposit a film that prevents flash rusting.

HEALTH AND SAFETY

Keep out of reach of children. For first aid and emergency, refer to Safety Data Sheet or contact the Poisons Information Centre on 131126.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

Available in: 300 mL

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI14-RF-300

Effective: November 2019

KH911192/1



AUSTRALIAN FAMILY OWNED SINCE 1989

