



PRODUCT DATA SHEET

RUBBER GREASE

PRODUCT DESCRIPTION

Rubber Grease is a premium quality clay thickened grease formulated with castor oil to provide outstanding performance in a wide range of automotive and industrial applications where contact with natural and/or synthetic rubber components is required or likely. Unlike mineral oil-based greases, the castor oil component of **Rubber Grease** means that it will not adversely affect rubber parts therefore preventing excessive softening or hardening.

By its very nature castor oil imparts excellent lubricity and corrosion prevention properties to **Rubber Grease**. A food grade antioxidant has been included to maximise in-service and storage life.

The state-of-the-art equipment and procedures employed to manufacture **Rubber Grease** imparts to this grease a high degree of mechanical and storage stability. It resists breakdown under high mechanical stress. In storage, it will not alter consistency or release oil.

Rubber Grease is an NLGI 2/3 consistency grease.

APPLICATION

Rubber Grease is recommended as a general purpose, non-harmful grease for automotive, industrial and consumer parts or components consisting of natural or synthetic rubber. These include hydraulic dust covers, braking system components, seals, washers, stoppers etc.

The recommended operating temperature range for **Rubber Grease** is from -5 °C to 120 °C.

Hi-Tec suggests that the equipment manufacturers' recommendations for grade, performance requirements and general operating conditions should be checked prior to use.

BENEFITS

- Compatible with natural & synthetic rubbers
- Excellent lubricity
- Protects against rust and corrosion
- Easy to apply
- Ingredients are non-harmful to environment
- Outstanding storage stability

HEALTH, SAFETY AND ENVIRONMENTAL

Rubber Grease is classified as non-hazardous. No special precautions are required if employed and handled in accordance to normal practice for this type of product. Good personal hygiene is recommended when handling this product. After any spills or personal contact, the skin area should be washed with soap and water. Clothing should be laundered. Additional health, safety and environmental information is available in the Material Safety Data Sheet which can be obtained by contacting Hi-Tec Oils.



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL PROPERTIES

Property	Results
Appearance	Red, smooth,
Thickener Type / Oil Base	Bentone / Vegetable Oils
Normal Temperature Range (°C)	-5 to 120
NLGI Classification	2/3
Drop Point (°C)	>260
Worked Penetration (mm/10)	250-280
Flash Point (°C)	>200

Available in: 18 kg, 2.5 kg and 450g tubs

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI7-1011

Effective: February 2020

MR022002/1



AUSTRALIAN FAMILY OWNED SINCE 1989

