

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

SEMI SYN 10W/40 SN/CF

PRODUCT DESCRIPTION

Semi Syn 10W/40 SN/CF is a premium quality API SN/CF engine oil. It is suitable for most types of petrol, diesel, and LPG four stroke engines under both severe and varied operating conditions. It is ideal for use in the professional workshop. The premium base oils help reduce engine oil oxidation, giving more protection from piston deposits compared to standard SN engine oils. Engine cleanliness is also promoted by the increased level of dispersants in **Semi Syn 10W/40 SN/CF**. Special additives inhibit the formation of sludge especially under the constant cold temperature operation of urban motoring.

Semi Syn 10W/40 SN/CF is excellent for cold starting as it has good fluidity characteristics and provides increased engine life, due to the decrease wear rates for both cams and bearings compared to less advanced oils. The high temperature performance of **Semi Syn 10W/40 SN/CF** is also enhanced by the selection of more thermally stable base oils, oxidation inhibitors, viscosity improvers and detergents. **Semi Syn 10W/40 SN/CF** is suitable for use in both low temperature stop-and-go driving, high speed high temperature motorway driving and engines with small clearances.

BENEFITS

- Improved oxidation resistance
- Protection from piston deposits
- Better wear protection
- Fast flow at cold temperature start up
- Protection at high temperatures

SPECIFICATIONS

Semi Syn 10W/40 SN/CF meets or exceeds the following demanding performance requirements:

API: SN, SM, SL, SJ, SH,CF, CD

Always consult your vehicle owner's manual for the manufacturer's recommendations.

TYPICAL PROPERTIES

Property	ASTM Method	Typical Results
Density (kg/Lt) @ 15°C	D-1298	0.864
Viscosity (cSt) @ 100°C	D-445	14.2
@ 40°C	D-445	93.3
Viscosity Index	D-2270	157
Flash Point; COC (°C)	D-92	219
Pour Point (°C)	D-97	-33
CCS @ -25°C (cP)	D-5293	6820

Available in: Bulk, 200 Litres, 60 Litres, 20 Litres, 10 Litres, 6 Litres, 5 Litres and 1 Litre









Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

ODUCT DATA SHEET

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI1-2123

Effective: July 2019

MR917011/1



