

Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362 5 Tarlington Place Smithfield NSW 2164 Correspondence: P.O Box 322 Castle Hill NSW 1765

Dorrespondence. F.O Box 322 Castle Hill NSW 1703

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

PRODUCT DATA SHEET

SLIDEWAY OILS ISO 32 - 680

PRODUCT DESCRIPTION

Slideway Oils are an upmarket lubricant recommended for slideways of machine tools, planers, lathes or guides of other types of machines where a tacky lubricant is required.

Slideway Oils are manufactured from the highest quality paraffinic base oils, non-corrosive EP additives and tackifier and is fully inhibited to protect against rust, oxidation and foam development.

Hi-Tec suggests that the equipment manufacturers' recommendations for viscosity grade, performance requirements and general operating conditions should be checked prior to use.

Property	Typical Results				
Item code (HI6-)	2562	2607	2606A	2605	2625
ISO Viscosity Grade	32	68	100	220	680
Density (kg/Lt) @ 15°C	0.875	0.889	0.891	0.900	0.919
Viscosity (cSt) @ 40°C	32.0	68.0	100.0	220.0	680.0
@100°C	8.0	9.4	11.1	20.6	40
Viscosity Index	102	106	96	110	97
Flash Point COC (°C)	240	243	262	265	268
Pour Point (°C)	-27	-24	-27	-24	-21
TAN (mg KOH/g)	0.60	0.61	0.60	0.61	0.60
Oxidation Characteristics-					
Hours to TAN 1.5	>1500	>1500	>1500	>1500	>1500
Rust Prevention -					
Salt Water at 48 Hours	Pass	Pass	Pass	Pass	Pass

Available in: Bulk, 1,000 Litres, 200 Litres, and 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Effective: March 2020

MR023030/1





