



PRODUCT DATA SHEET

SOLCUT QLB2

APPLICATION

Solcut QLB2 can be used in a wide range of applications, from brass and aluminium machining in large transfer systems to machining steel in small single sump machines.

Solcut QLB2 is a semi-synthetic biostable machining and grinding fluid forming transparent emulsions, which may become semi-translucent in hard water. **Solcut QLB2** combines the cleanliness and detergency of synthetic products without the sticky residues often encountered with such products.

USAGE

Use **Solcut QLB2** at concentrations varying between 2% and 5% depending on the machining application but in general grinding is satisfactory at 2% concentration and other machining applications require between 3% and 4% concentration. For brass machining, good results have been had at concentrations of 6% and for aluminum 10%.

BENEFITS

- Emulsions of **Solcut QLB2** are non-staining to aluminum.
- Excellent ferrous corrosion protection.
- Offers increased cleanliness and longer sump life.
- For emulsions using **Solcut QLB2** under normal conditions, 90% of any tramp oil will float out over a week-end shutdown. This enables the tramp oil to be readily removed and thus further extends the sump life of the emulsion.
- In common with the rest of Hi-Tec's biostable cutting fluids, **Solcut QLB2** emulsions can readily be split with conventional effluent treatment techniques, thus minimizing disposal costs.

COMPATIBILITY

Solcut QLB2 is compatible with most commonly used polymer hose and seal materials. However, due to the wide variety of materials available, specific recommendations should be sought from your distributor or Hi-Tec Sales Representative.

STORAGE

If the following criteria are adhered to, **Solcut QLB2** can be stored for at least six months.

Maximum recommended long-term storage temperature: 40°C.

Minimum recommended long-term storage temperature: 0°C.

Keep drums/containers tightly closed when not in use.

Store containers/drums in a dry and well ventilated area.

Hi-Tec suggests that the equipment manufacturers' recommendations for performance requirements and general operating conditions should be checked prior to use.



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

TYPICAL PROPERTIES

Property

Appearance

Specific Gravity @ 25°C

pH of 5% emulsion in water

pH Neat

Acid Value

Total Alkalinity

Refractometer Factor

Results

Fluorescent green liquid

1.005 – 1.015

9.7 - 10.2

10.0 - 10.7

45.0 - 55.0 mg KOH/g

90 - 105 mg KOH/g

0.5

Available in: 200 Litres, 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item code: HI6-2930

Effective: February 2020

GH022041/1



AUSTRALIAN FAMILY OWNED SINCE 1989

