



PRODUCT DATA SHEET

SYN MTF 75W/90 GL-4

PRODUCT DESCRIPTION

Syn MTF 75W/90 GL-4 is a full synthetic poly-alpha-olefin manual transmission oil which offers outstanding high temperature and high load performance properties combined with excellent low temperature fluidity and cold flow properties, excellent corrosion protection and superior seal compatibility.

Syn MTF 75W/90 GL-4 is an API GL-4 gear lubricant specially recommended for synchronised manual transmissions, front wheel drive transaxles gear boxes, transfer cases, automotive hypoid and spiral bevel operating at low to moderate speeds for selected Ford, Fiat, Maserati, Jaguar, Jeep, Lamborghini Tata and Toyota vehicles as well as many others where the manufacturer specifies the use of a Synthetic API GL-4, SAE 75W-90 gear oil.

Syn MTF 75W/90 GL-4 is specifically designed to provide very much improved:

- Oil seal life
- Durability (gear surface life)
- Corrosion protection to yellow metals under both wet and dry conditions
- Extended Drain Intervals

SPECIFICATIONS

Syn MTF 75W/90 GL-4 meets or exceeds API GL-4

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

NOTE: Do not use where a Synthetic 75W90 API GL5 is specified

TYPICAL PROPERTIES

| Property | ASTM Method | Typical Results |
|-----------------------------|-------------|-----------------|
| Appearance | Visual | Dark Blue |
| Density (kg/Lt) @ 15°C | D-1298 | 0.857 |
| Viscosity, cSt at 40°C | D-445 | 102.3 |
| at 100°C | D-445 | 14.4 |
| Viscosity Index | D-2270 | 145 |
| Flash Point; PM Closed (°C) | D-93 | 170 |
| Pour Point (°C) | D-97 | -41 |
| Sulphated Ash (% wt) | D-482 | <0.01 |
| Sulphur (% wt) | D-129 | 0.81 |
| Phosphorus (% wt) | D-1091 | 0.24 |

Available in: Bulk, 1000 Litres, 200 Litres, 20 Litres, 4 Litres

“Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au”

Item Code: HI4-2481

Effective: September 2022

RS229010/1



AUSTRALIAN FAMILY OWNED SINCE 1989

