



Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

SYNPLUS 10W/50 SN

PRODUCT DESCRIPTION

Synplus 10W/50 SN is a full synthetic, low SAPS, super high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection.

Today's environmentally conscious market demands reduced emissions and increased fuel efficiency. This has led to the development of new engine designs resulting in demands for higher quality lubricants.

In recent years car manufacturers have developed smaller, higher output engines to meet stricter fuel economy limits. Small engines help decrease vehicle weight and improve economy but these engines impact lubricants through:

- **Increased heat** - accelerates the rate of oil oxidation, nitration and deposit formation. This degrades the oil and encourages the creation of more acid and increases viscosity.
- **Increased pressure and speed** - makes it harder for the oil to maintain a lubricant film to prevent metal on metal contact. This accelerates valve train wear.
- **Emission Control** - most of today's petrol engines are fitted with three way catalytic converters which reduce emissions of CO, NOx and unburned carbon. These catalytic converters comprise a Reduction Catalyst, which converts NOx to harmless Nitrogen, and an Oxidation Catalyst which burns the CO and hydrocarbons. Catalytic converters however are susceptible to SAPS (Sulfated Ash, Phosphorous and Sulfur) which are present in engine oil detergents and antiwear additives and in base oils.

Synplus 10W/50 SN is designed to meet all these challenges to the lubricant systems.

SPECIFICATIONS:

Synplus 10W/50 SN meets or exceeds the following demanding performance requirements:

API:	SN, SM, SL, CF, CE, CD
ACEA:	A3/B3, A3/B4, C3
Mercedes Benz:	229.31, 229.51
Renault:	0700, 0710

API SN: the newest passenger car gasoline engine oil service category requiring improved oxidation resistance and deposit protection (which today's smaller higher output engines demand), better wear protection for valve trains and reduced evaporative loss with less requirement for top up oil. API SN oils provide better low-temperature performance over the life of the oil, extended oil drain intervals in line with the engine manufacturers' recommendations and extended life for catalytic converters.

ACEA A3/B4: **Synplus 10W/50 SN** meets the requirements of the Association of European Automobile Constructors (ACEA) A3/B4 grade which calls for stable, stay in grade oil for use in high performance gasoline and direct injection diesel engines and car or light van diesel engines. The A3/B4 oils may be used for extended drain intervals where specified by the engine manufacturer and/or as year round lower viscosity oils and/or for severe conditions as defined by the engine manufacturer.



AUSTRALIAN FAMILY OWNED SINCE 1989





Hi-Tec Oil Traders Pty Ltd ABN 28 053 837 362

5 Tarlington Place Smithfield NSW 2164

Correspondence: P.O Box 322 Castle Hill NSW 1765

Ph: 1300 796 009 | Fax: (02) 9604 1611 | Email: hitecoils@hi-tecoils.com.au

www.hi-tecoils.com.au

PRODUCT DATA SHEET

ACEA C3: Synplus 10W/50 SN may also be used where oil meeting ACEA C3 is specified. ACEA C3 calls for stable stay-in-grade oils intended for use as a catalyst compatible lubricants in vehicles with Diesel Particulate Filters (DPF) and Three Way Catalysts (TWC) in high performance car and light van diesel and gasoline engines. These oils will help prolong the life of the DPF and TWC.

DaimlerChrysler MB229.51: Synplus 10W/50 SN can be used where MB229.51 is called for. The synthetic formulation meets the extended drain requirements of Mercedes Benz. Its lower volatility will reduce the evaporation of lighter oil fractions which would lead to oil thickening, contaminant concentration and increased oil consumption.

Always consult your vehicle owner's manual for the manufacturer's lubricant recommendations.

TYPICAL PROPERTIES

Property	Results
Appearance	Amber
Density (kg/Lt) @15°C	0.858
Viscosity (cSt) @100°C	17.3
@40°C	109
Viscosity Index	174
HTHS (cP)	3.7
TBN (mg KOH/g)	7.3
Sulphated Ash (% wt)	0.77
Phosphorus (% wt)	0.08
Sulphur (% wt)	0.2
Flash Point (°C)	220

Available in: Bulk, 1000 Litres, 200 Litres and 20 Litres

"Hi-Tec Oil Traders Pty Ltd (Hi-Tec Oils) has endeavoured to ensure that all information, representations and specifications contained in this product data sheet are accurate at the time of publication. This general information should be used in conjunction with appropriate inquiries by users of the product including consultation with the vehicle or equipment manufacturers published information.

It is the responsibility of users of the product to use the product safely. Users should consult the safety data sheets for each product at www.hi-tecoils.com.au. Hi-Tec Oils takes no responsibility for injury or damage if the product is used in an inappropriate or unsafe manner.

Our product warranty and product quality statement can be viewed at www.hi-tecoils.com.au"

Item Code: HI1-2098

Effective: March 2022

MR223003/1



AUSTRALIAN FAMILY OWNED SINCE 1989

